

# Package ‘MVar’

June 21, 2026

**Type** Package

**Title** Multivariate Analysis

**Version** 2.3.0

**Date** 2026-06-21

**Imports** graphics, grDevices, MASS, stats

**Description** Multivariate analysis, having functions that perform simple correspondence analysis (CA) and multiple correspondence analysis (MCA), principal components analysis (PCA), canonical correlation analysis (CCA), factorial analysis (FA), multidimensional scaling (MDS), linear (LDA) and quadratic discriminant analysis (QDA), hierarchical and non-hierarchical cluster analysis, simple and multiple linear regression, multiple factor analysis (MFA) for quantitative, qualitative, frequency (MFACT) and mixed data, biplot, scatter plot, projection pursuit (PP), grant tour method and other useful functions for the multivariate analysis.

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**NeedsCompilation** yes

**Author** Paulo Cesar Ossani [aut, cre] (ORCID:  
<<https://orcid.org/0000-0002-6617-8085>>),  
Marcelo Angelo Cirillo [aut] (ORCID:  
<<https://orcid.org/0000-0002-2647-439X>>)

**Maintainer** Paulo Cesar Ossani <[ossanipc@hotmail.com](mailto:ossanipc@hotmail.com)>

**Repository** CRAN

**Date/Publication** 2026-06-21 18:20:02 UTC

## Contents

MVar-package . . . . .	2
Biplot . . . . .	6
CA . . . . .	8
CCA . . . . .	9

CI . . . . .	11
Cluster . . . . .	13
CoefVar . . . . .	15
DA . . . . .	16
DataCoffee . . . . .	18
DataFreq . . . . .	19
DataInd . . . . .	20
DataMix . . . . .	21
DataQuali . . . . .	21
DataQuan . . . . .	22
FA . . . . .	23
GrandTour . . . . .	25
GSVD . . . . .	27
IM . . . . .	28
LocLab . . . . .	29
MDS . . . . .	30
MFA . . . . .	31
NormData . . . . .	34
NormTest . . . . .	35
PCA . . . . .	36
Plot.CA . . . . .	37
Plot.CCA . . . . .	39
Plot.CI . . . . .	41
Plot.Cor . . . . .	42
Plot.FA . . . . .	43
Plot.MFA . . . . .	45
Plot.PCA . . . . .	46
Plot.PP . . . . .	48
Plot.Regr . . . . .	51
PP_Index . . . . .	52
PP_Optimizer . . . . .	55
Regr . . . . .	58
Scatter . . . . .	60
<b>Index</b>	<b>62</b>

---

MVar-package

*Multivariate Analysis.*


---

## Description

Multivariate analysis, having functions that perform simple correspondence analysis (CA) and multiple correspondence analysis (MCA), principal components analysis (PCA), canonical correlation analysis (CCA), factorial analysis (FA), multidimensional scaling (MDS), linear (LDA) and quadratic discriminant analysis (QDA), hierarchical and non-hierarchical cluster analysis, simple and multiple linear regression, multiple factor analysis (MFA) for quantitative, qualitative, frequency (MFACT) and mixed data, biplot, scatter plot, projection pursuit (PP), grant tour method and other useful functions for the multivariate analysis.

**Details**

Package: MVar  
Type: Package  
Version: 2.3.0  
Date: 2026-06-21  
License: GPL(>=2)  
LazyLoad: yes

**Author(s)**

Paulo Cesar Ossani and Marcelo Angelo Cirillo.  
Maintainer: Paulo Cesar Ossani <ossanipc@hotmail.com>

**References**

- Abdessemed, L.; Escofier, B.; Analyse factorielle multiple de tableaux de frequencies: comparaison avec l'analyse canonique des correspondences. *Journal de la Societe de Statistique de Paris*, Paris, v. 137, n. 2, p. 3-18, 1996.
- Abdi, H. Singular Value Decomposition (SVD) and Generalized Singular Value Decomposition (GSVD). In: SALKIND, N. J. (Ed.). *Encyclopedia of measurement and statistics*. Thousand Oaks: Sage, 2007. p. 907-912.
- Abdi, H.; Valentin, D. Multiple factor analysis (MFA). In: SALKIND, N. J. (Ed.). *Encyclopedia of measurement and statistics*. Thousand Oaks: Sage, 2007. p. 657-663.
- Abdi, H.; Williams, L. Principal component analysis. *WIREs Computational Statistics*, New York, v. 2, n. 4, p. 433-459, July/Aug. 2010.
- Abdi, H.; Williams, L.; Valentin, D. Multiple factor analysis: principal component analysis for multitable and multiblock data sets. *WIREs Computational Statistics*, New York, v. 5, n. 2, p. 149-179, Feb. 2013.
- Asimov, D. The Grand Tour: A Tool for Viewing Multidimensional Data. *SIAM Journal of Scientific and Statistical Computing*, 6(1), 128-143, 1985.
- Asimov, D.; Buja, A. The grand tour via geodesic interpolation of 2-frames. in *Visual Data Exploration and Analysis. Symposium on Electronic Imaging Science and Technology*, IS&T/SPIE. 1994.
- Becue-Bertaut, M.; Pages, J. A principal axes method for comparing contingency tables: MFACT. *Computational Statistics & Data Analysis*, New York, v. 45, n. 3, p. 481-503, Feb. 2004
- Becue-Bertaut, M.; Pages, J. Multiple factor analysis and clustering of a mixture of quantitative, categorical and frequency data. *Computational Statistics & Data Analysis*, New York, v. 52, n. 6, p. 3255-3268, Feb. 2008.
- Benzecri, J. Analyse de l'inertie intraclasse par l'analyse d'un tableau de contingence: intra-classinertia analysis through the analysis of a contingency table. *Les Cahiers de l'Analyse des Donnees*, Paris, v. 8, n. 3, p. 351-358, 1983.

- Buja, A.; Asimov, D. Grand tour methods: An outline. *Computer Science and Statistics*, 17:63-67. 1986.
- Buja, A.; Cook, D.; Asimov, D.; Hurley, C. Computational Methods for High-Dimensional Rotations in Data Visualization, in C. R. Rao, E. J. Wegman & J. L. Solka, eds, "*Handbook of Statistics: Data Mining and Visualization*", Elsevier/North Holland, <http://www.elsevier.com>, pp. 391-413. 2005.
- Charnet, R., et al. *Análise de modelos de regressão linear*, 2a ed. Campinas: Editora da Unicamp, 2008. 357 p.
- Cook, D.; Lee, E. K.; Buja, A.; Wickham, M. H. Grand tours, projection pursuit guided tours and manual controls. In Chen, Chunhou, Hardle, Wolfgang, Unwin, e Antony (Eds.), *Handbook of Data Visualization*, Springer Handbooks of Computational Statistics, chapter III.2, p. 295-314. Springer, 2008.
- Cook, D.; Buja, A.; Cabrera, J. Projection pursuit indexes based on orthonormal function expansions. *Journal of Computational and Graphical Statistics*, 2(3):225-250, 1993.
- Cook, D.; Buja, A.; Cabrera, J.; Hurley, C. Grand tour and projection pursuit, *Journal of Computational and Graphical Statistics*, 4(3), 155-172, 1995.
- Cook, D.; Swayne, D. F. *Interactive and Dynamic Graphics for Data Analysis: With R and GGobi*. Springer. 2007.
- Escofier, B. Analyse factorielle en référence à un modèle: application à l'analyse d'un tableau d'échanges. *Revue de Statistique Appliquée*, Paris, v. 32, n. 4, p. 25-36, 1984.
- Escofier, B.; Drouot, D. Analyse des différences entre plusieurs tableaux de fréquence. *Les Cahiers de l'Analyse des Données*, Paris, v. 8, n. 4, p. 491-499, 1983.
- Escofier, B.; Pages, J. *Analyse factorielles simples et multiples*. Paris: Dunod, 1990. 267 p.
- Escofier, B.; Pages, J. *Analyses factorielles simples et multiples: objectifs, méthodes et interprétation*. 4th ed. Paris: Dunod, 2008. 318 p.
- Escofier, B.; Pages, J. *Comparaison de groupes de variables définies sur le même ensemble d'individus: un exemple d'applications*. Le Chesnay: Institut National de Recherche en Informatique et en Automatique, 1982. 121 p.
- Escofier, B.; Pages, J. Multiple factor analysis (AFUMULT package). *Computational Statistics & Data Analysis*, New York, v. 18, n. 1, p. 121-140, Aug. 1994
- Espezua, S.; Villanueva, E.; Maciel, C. D.; Carvalho, A. A projection pursuit framework for supervised dimension reduction of high dimensional small sample datasets. *Neurocomputing*, 149, 767-776, 2015.
- Ferreira, D. F. *Estatística multivariada*. 2. ed. rev. e ampl. Lavras: UFLA, 2011. 675 p.
- Friedman, J. H., Tukey, J. W. A projection pursuit algorithm for exploratory data analysis. *IEEE Transaction on Computers*, 23(9):881-890, 1974.
- Greenacre, M.; Blasius, J. *Multiple correspondence analysis and related methods*. New York: Taylor and Francis, 2006. 607 p.
- Hastie, T.; Buja, A.; Tibshirani, R. Penalized discriminant analysis. *The Annals of Statistics*. 23(1), 73-102. 1995.
- Hotelling, H. Analysis of a complex of statistical variables into principal components. *Journal of Educational Psychology*, Arlington, v. 24, p. 417-441, Sept. 1933.

- Huber, P. J. Projection pursuit. *Annals of Statistics*, 13(2):435-475, 1985.
- Hurley, C.; Buja, A. Analyzing high-dimensional data with motion graphics, *SIAM Journal of Scientific and Statistical Computing*, 11 (6), 1193-1211. 1990.
- Johnson, R. A.; Wichern, D. W. *Applied multivariate statistical analysis*. 6th ed. New Jersey: Prentice Hall, 2007. 794 p.
- Jones, M. C.; Sibson, R. What is projection pursuit, (with discussion), *Journal of the Royal Statistical Society, Series A* 150, 1-36, 1987.
- Lee, E.; Cook, D.; Klinke, S.; Lumley, T. Projection pursuit for exploratory supervised classification. *Journal of Computational and Graphical Statistics*, 14(4):831-846, 2005.
- Lee, E. K., Cook, D. A projection pursuit index for large p small n data. *Statistics and Computing*, 20(3):381-392, 2010.
- Martinez, W. L.; Martinez, A. R. *Computational Statistics Handbook with MATLAB*, 2th. ed. New York: Chapman & Hall/CRC, 2007. 794 p.
- Martinez, W. L.; Martinez, A. R.; Solka, J. *Exploratory Data Analysis with MATLAB*, 2th. ed. New York: Chapman & Hall/CRC, 2010. 499 p.
- Mingoti, S. A. *Analise de dados atraves de metodos de estatistica multivariada: uma abordagem aplicada*. Belo Horizonte: UFMG, 2005. 297 p.
- Ossani, P. C.; Cirillo, M. A.; Borem, F. M.; Ribeiro, D. E.; Cortez, R. M. Quality of specialty coffees: a sensory evaluation by consumers using the MFACT technique. *Revista Ciencia Agronomica (UFC. Online)*, v. 48, p. 92-100, 2017.
- Ossani, P. C. *Qualidade de cafes especiais e nao especiais por meio da analise de multiplos fatores para tabelas de contingencias*. 2015. 107 p. Dissertacao (Mestrado em Estatistica e Experimentacao Agropecuaria) - Universidade Federal de Lavras, Lavras, 2015.
- Pages, J. Analyse factorielle multiple appliquee aux variables qualitatives et aux donnees mixtes. *Revue de Statistique Appliquee*, Paris, v. 50, n. 4, p. 5-37, 2002.
- Pages, J. Multiple factor analysis: main features and application to sensory data. *Revista Colombiana de Estadistica*, Bogota, v. 27, n. 1, p. 1-26, 2004.
- Pena, D.; Prieto, F. Cluster identification using projections. *Journal of the American Statistical Association*, 96(456):1433-1445, 2001.
- Posse, C. Projection pursuit exploratory data analysis, *Computational Statistics and Data Analysis*, 29:669-687, 1995a.
- Posse, C. Tools for two-dimensional exploratory projection pursuit, *Journal of Computational and Graphical Statistics*, 4:83-100, 1995b
- Rencher, A.C.; *Methods of Multivariate Analysis*. 2th. ed. New York: J.Wiley, 2002. 708 p.
- Young, F. W.; Rheingans P. Visualizing structure in high-dimensional multivariate data, *IBM Journal of Research and Development*, 35:97-107, 1991.
- Young, F. W.; Faldowski R. A.; McFarlane M. M. *Multivariate statistical visualization, in Handbook of Statistics*, Vol 9, C. R. Rao (ed.), The Netherlands: Elsevier Science Publishers, 959-998, 1993.

---

 Biplot

*Biplot graph.*


---

### Description

Plots the Biplot graph.

### Usage

```
Biplot(data, alpha = 0.5, title = NA, xlabel = NA, ylabel = NA,
       size = 1.1, grid = TRUE, color = TRUE, var = TRUE,
       obs = TRUE, linlab = NA, class = NA, classcolor = NA,
       posleg = 2, boxleg = TRUE, axes = TRUE, savptc = FALSE,
       width = 3236, height = 2000, res = 300)
```

### Arguments

data	Data for plotting.
alpha	Representativeness of the individuals (alpha), representativeness of the variables (1 - alpha), being 0.5 the default.
title	Titles of the graphics, if not set, assumes the default text.
xlabel	Names the X axis, if not set, assumes the default text.
ylabel	Names the Y axis, if not set, assumes the default text.
size	Size of the points in the graphs.
grid	Put grid on graphs (default = TRUE).
color	Colored graphics (default = TRUE).
var	Adds the variable projections to graph (default = TRUE).
obs	Adds the observations to graph (default = TRUE).
linlab	Vector with the labels for the observations.
class	Vector with names of data classes.
classcolor	Vector with the colors of the classes.
posleg	0 with no caption, 1 for caption in the left upper corner, 2 for caption in the right upper corner (default), 3 for caption in the right lower corner, 4 for caption in the left lower corner.
boxleg	Puts the frame in the caption (default = TRUE).
axes	Plots the X and Y axes (default = TRUE).
savptc	Saves graphics images to files (default = FALSE).
width	Graphics images width when savptc = TRUE (default = 3236).
height	Graphics images height when savptc = TRUE (default = 2000).
res	Nominal resolution in ppi of the graphics images when savptc = TRUE (default = 300).

**Value**

Biplot	Biplot graph.
Md	Matrix eigenvalues.
Mu	Matrix U (eigenvectors).
Mv	Matrix V (eigenvectors).
coorI	Coordinates of the individuals.
coorV	Coordinates of the variables.
pvar	Proportion of the principal components.

**Author(s)**

Paulo Cesar Ossani  
Marcelo Angelo Cirillo

**References**

Rencher, A. C. *Methods of multivariate analysis*. 2th. ed. New York: J.Wiley, 2002. 708 p.

**Examples**

```
data(iris) # dataset

data <- iris[,1:4]

Biplot(data)

cls <- iris[,5]
res <- Biplot(data, alpha = 0.6, title = "Biplot of data valuing individuals",
             class = cls, classcolor = c("goldenrod3", "gray56", "red"),
             posleg = 2, boxleg = FALSE, axes = TRUE, savptc = FALSE,
             width = 3236, height = 2000, res = 300)
print(res$pvar)

res <- Biplot(data, alpha = 0.4, title = "Graph valuing the variables",
             xlabel = "", ylabel = "", color = FALSE, obs = FALSE,
             savptc = FALSE, width = 3236, height = 2000, res = 300)
print(res$pvar)
```

CA

*Correspondence Analysis (CA).***Description**

Performs simple correspondence analysis (CA) and multiple (MCA) in a data set.

**Usage**

```
CA(data, typdata = "f", typmatrix = "I")
```

**Arguments**

<code>data</code>	Data to be analyzed (contingency table).
<code>typdata</code>	"f" for frequency data (default), "c" for qualitative data.
<code>typmatrix</code>	Matrix used for calculations when <code>typdata = "c"</code> . "I" for indicator matrix (default), "B" for Burt's matrix.

**Value**

<code>depdata</code>	Verify if the rows and columns are dependent, or independent by the chi-square test, at the 5% significance level.
<code>typdata</code>	Data type: "F" frequency or "C" qualitative.
<code>numcod</code>	Number of principal components.
<code>mtxP</code>	Matrix of the relative frequency.
<code>vtrR</code>	Vector with sums of the rows.
<code>vtrC</code>	Vector with sums of the columns.
<code>mtxPR</code>	Matrix with profile of the rows.
<code>mtxPC</code>	Matrix with profile of the columns.
<code>mtxZ</code>	Matrix Z.
<code>mtxU</code>	Matrix with the eigenvectors U.
<code>mtxV</code>	Matrix with the eigenvectors V.
<code>mtxL</code>	Matrix with eigenvalues.
<code>mtxX</code>	Matrix with the principal coordinates of the rows.
<code>mtxY</code>	Matrix with the principal coordinates of the columns.
<code>mtxAutv1r</code>	Matrix of the inertias (variances), with the proportions and proportions accumulated.

**Author(s)**

Paulo Cesar Ossani

Marcelo Angelo Cirillo

**References**

Mingoti, S. A. *Analise de dados atraves de metodos de estatistica multivariada: uma abordagem aplicada*. Belo Horizonte: UFMG, 2005. 297 p.

Rencher, A. C. *Methods of multivariate analysis*. 2th. ed. New York: J.Wiley, 2002. 708 p.

**See Also**

[Plot.CA](#)

**Examples**

```
data(DataFreq) # frequency data set

data <- DataFreq[,2:ncol(DataFreq)]

rownames(data) <- as.character(t(DataFreq[1:nrow(DataFreq),1]))

res <- CA(data = data, "f") # performs CA

print("Is there dependency between rows and columns?"); res$depdata

print("Number of principal coordinates:"); res$numcoord

print("Principal coordinates of the rows:"); round(res$mtxX,2)

print("Principal coordinates of the columns:"); round(res$mtxY,2)

print("Inertia of the principal components:"); round(res$mtxAutvlr,2)
```

---

CCA

*Canonical Correlation Analysis(CCA)*.

---

**Description**

Perform Canonical Correlation Analysis (CCA) on a data set.

**Usage**

```
CCA(X = NULL, Y = NULL, type = 1, test = "Bartlett", sign = 0.05)
```

**Arguments**

X	First group of variables of a data set.
Y	Second group of variables of a data set.
type	1 for analysis using the covariance matrix (default), 2 for analysis using the correlation matrix.
test	Test of significance of the relationship between the group X and Y: "Bartlett" (default) or "Rao".
sign	Test significance level (default 5%).

**Value**

Cxx	Covariance matrix or correlation Cxx.
Cyy	Covariance matrix or correlation Cyy.
Cxy	Covariance matrix or correlation Cxy.
Cyx	Covariance matrix or correlation Cyx.
var.UV	Matrix with eigenvalues (variances) of the canonical pairs U and V.
corr.UV	Matrix of the correlation of the canonical pairs U and V.
coef.X	Matrix of the canonical coefficients of the group X.
coef.Y	Matrix of the canonical coefficients of the group Y.
corr.X	Matrix of the correlations between canonical variables and the original variables of the group X.
corr.Y	Matrix of the correlations between the canonical variables and the original variables of the group Y.
score.X	Matrix with the scores of the group X.
score.Y	Matrix with the scores of the group Y.
sigtest	Returns the significance test of the relationship between group X and Y: "Bartlett" (default) or "Rao".

**Author(s)**

Paulo Cesar Ossani  
Marcelo Angelo Cirillo

**References**

- Mingoti, S. A. *Análise de dados através de métodos de estatística multivariada: uma abordagem aplicada*. Belo Horizonte: UFMG, 2005. 297 p.
- Ferreira, D. F. *Estatística Multivariada*. 2a ed. revisada e ampliada. Lavras: Editora UFLA, 2011. 676 p.
- Rencher, A. C. *Methods of multivariate analysis*. 2th. ed. New York: J.Wiley, 2002. 708 p.
- Lattin, J.; Carrol, J. D.; Green, P. E. *Análise de dados multivariados*. 1th. ed. Sao Paulo: Cengage Learning, 2011. 455 p.

**See Also**[Plot.CCA](#)**Examples**

```
data(DataMix) # data set

data <- DataMix[,2:ncol(DataMix)]

rownames(data) <- DataMix[,1]

X <- data[,1:2]

Y <- data[,5:6]

res <- CCA(X, Y, type = 2, test = "Bartlett", sign = 0.05)

print("Matrix with eigenvalues (variances) of the canonical pairs U and V:"); round(res$var.UV,3)

print("Matrix of the correlation of the canonical pairs U and V:"); round(res$corr.UV,3)

print("Matrix of the canonical coefficients of the group X:"); round(res$coef.X,3)

print("Matrix of the canonical coefficients of the group Y:"); round(res$coef.Y,3)

print("Matrix of the correlations between the canonical
      variables and the original variables of the group X:"); round(res$corr.X,3)

print("Matrix of the correlations between the canonical
      variables and the original variables of the group Y:"); round(res$corr.Y,3)

print("Matrix with the scores of the group X:"); round(res$score.X,3)

print("Matrix with the scores of the group Y:"); round(res$score.Y,3)

print("test of significance of the canonical pairs:"); res$sigtest
```

---

CI

*Confidence Intervals: Univariate and Multivariate.*

---

**Description**

Computes univariate and multivariate confidence intervals for variables in a dataset.

**Usage**

```
CI(data, sigma = NA, conf = 0.95, type = "T")
```

**Arguments**

data	Data used to compute the confidence intervals.
sigma	Variance–covariance matrix; otherwise the CI will be based on the sample variance (default sigma = NA).
conf	Confidence level of the CI (default conf = 95%).
type	Type of interval: 'T' for Hotelling's $(T^2)$ or 'B' for Bonferroni.

**Value**

CIu	Univariate confidence interval with confidence level 'conf'.
CI m	Multivariate confidence interval with confidence level 'conf'.

**Author(s)**

Paulo Cesar Ossani

**References**

- Ferreira, D. F. *Estatística Multivariada*. 2a ed. revisada e ampliada. Lavras: Editora UFLA, 2011. 676 p.
- Rencher, A. C. *Methods of multivariate analysis*. 2th. ed. New York: J.Wiley, 2002. 708 p.. 708 p.

**See Also**

[Plot.CI](#)

**Examples**

```
data(iris) # data set

# Interval with unknown population variance
res <- CI(data = iris[,1:4], sigma = NA, conf = 0.95, type = 'T')
# res <- CI(data = iris[,1:4], sigma = NA, conf = 0.95, type = 'B')

res$ciu # Univariate interval
res$cim # Multivariate interval

# Interval with known population variance
sig <- matrix(c(5.286, 0.942, 1.274, 4.516, # Example of known variance matrix
              0.942, 3.690, 0.730, 1.122,
              1.274, 0.730, 7.116, 1.296,
              4.516, 1.122, 1.296, 4.581),
             nrow = 4, byrow = TRUE)

# res <- CI(data = iris[,1:4], sigma = sig, conf = 0.95, type = 'T')
res <- CI(data = iris[,1:4], sigma = sig, conf = 0.95, type = 'B')

res$ciu # Univariate interval
res$cim # Multivariate interval
```

---

Cluster *Cluster Analysis.*

---

### Description

Performs hierarchical and non-hierarchical cluster analysis in a data set.

### Usage

```
Cluster(data, titles = NA, hierarquic = TRUE, analysis = "Obs",
        cor.abs = FALSE, normalize = FALSE, distance = "euclidean",
        method = "complete", horizontal = FALSE, num.groups = 0,
        lambda = 2, savptc = FALSE, width = 3236, height = 2000,
        res = 300, casc = TRUE)
```

### Arguments

data	Data to be analyzed.
titles	Titles of the graphics, if not set, assumes the default text.
hierarquic	Hierarchical groupings (default = TRUE), for non-hierarchical groupings (method K-Means), only for case 'analysis' = "Obs".
analysis	"Obs" for analysis on observations (default), "Var" for analysis on variables.
cor.abs	Matrix of absolute correlation case 'analysis' = "Var" (default = FALSE).
normalize	Normalize the data only for case 'analysis' = "Obs" (default = FALSE).
distance	Metric of the distances in case of hierarchical groupings: "euclidean" (default), "maximum", "manhattan", "canberra", "binary" or "minkowski". Case Analysis = "Var" the metric will be the correlation matrix, according to cor.abs.
method	Method for analyzing hierarchical groupings: "complete" (default), "ward.D", "ward.D2", "single", "average", "mcquitty", "median" or "centroid".
horizontal	Horizontal dendrogram (default = FALSE).
num.groups	Number of groups to be formed.
lambda	Value used in the minkowski distance.
savptc	Saves graphics images to files (default = FALSE).
width	Graphics images width when savptc = TRUE (default = 3236).
height	Graphics images height when savptc = TRUE (default = 2000).
res	Nominal resolution in ppi of the graphics images when savptc = TRUE (default = 300).
casc	Cascade effect in the presentation of the graphics (default = TRUE).

**Value**

Several graphics.

tab.res	Table with similarities and distances of the groups formed.
groups	Original data with groups formed.
res.groups	Results of the groups formed.
R.sqt	Result of the R squared.
sum.sqt	Total sum of squares.
mtx.dist	Matrix of the distances.

**Author(s)**

Paulo Cesar Ossani

**References**

- Rencher, A. C. *Methods of multivariate analysis*. 2th. ed. New York: J.Wiley, 2002. 708 p.
- Mingoti, S. A. *análise de dados através de métodos de estatística multivariada: uma abordagem aplicada*. Belo Horizonte: UFMG, 2005. 297 p.
- Ferreira, D. F. *Estatística Multivariada*. 2a ed. revisada e ampliada. Lavras: Editora UFLA, 2011. 676 p.

**Examples**

```
data(DataQuan) # set of quantitative data

data <- DataQuan[,2:8]

rownames(data) <- DataQuan[1:nrow(DataQuan),1]

res <- Cluster(data, titles = NA, hierarquic = TRUE, analysis = "Obs",
              cor.abs = FALSE, normalize = FALSE, distance = "euclidean",
              method = "ward.D", horizontal = FALSE, num.groups = 2,
              savptc = FALSE, width = 3236, height = 2000, res = 300,
              casc = FALSE)

print("R squared:"); res$R.sqt
# print("Total sum of squares:"); res$sum.sqt
print("Groups formed:"); res$groups
# print("Table with similarities and distances:"); res$tab.res
# print("Table with the results of the groups:"); res$res.groups
# print("Distance Matrix:"); res$mtx.dist

write.table(file=file.path(tempdir(),"SimilarityTable.csv"), res$tab.res, sep=";",
            dec=".",row.names = FALSE)
write.table(file=file.path(tempdir(),"GroupData.csv"), res$groups, sep=";",
            dec=".",row.names = TRUE)
write.table(file=file.path(tempdir(),"GroupResults.csv"), res$res.groups, sep=";",
            dec=".",row.names = TRUE)
```

---

CoefVar	<i>Coefficient of variation of the data.</i>
---------	--

---

**Description**

Find the coefficient of variation of the data, either overall or per column.

**Usage**

```
CoefVar(data, type = 1)
```

**Arguments**

data	Data to be analyzed.
type	1 Coefficient of overall variation (default), 2 Coefficient of variation per column.

**Value**

Coefficient of variation, either overall or per column.

**Author(s)**

Paulo Cesar Ossani  
Marcelo Angelo Cirillo

**References**

Ferreira, D. F.; *Estatística Básica*. 2 ed. rev. Lavras: UFLA, 2009. 664 p.

**Examples**

```
data(DataQuan) # data set  
data <- DataQuan[,2:8]  
  
res <- CoefVar(data, type = 1) # Coefficient of overall variation  
round(res,2)  
  
res <- CoefVar(data, type = 2) # Coefficient of variation per column  
round(res,2)
```

---

DA *Linear (LDA) and quadratic discriminant analysis (QDA).*

---

### Description

Perform linear and quadratic discriminant analysis.

### Usage

```
DA(data, class = NA, type = "lda", validation = "learning",
    method = "moment", prior = NA, testing = NA)
```

### Arguments

data	Data to be classified.
class	Vector with data classes names.
type	"lda": linear discriminant analysis (default), or "qda": quadratic discriminant analysis.
validation	Type of validation: "learning" - data training (default), or "testing" - classifies the data of the vector "testing".
method	Classification method: "mle" to MLEs, "mve" to use cov.mv, "moment" (default) for standard mean and variance estimators, or "t" for robust estimates based on the t distribution.
prior	Probabilities of occurrence of classes. If not specified, it will take the proportions of the classes. If specified, probabilities must follow the order of factor levels.
testing	Vector with indices that will be used in data as test. For validation = "learning", one has testing = NA.

### Value

confusion	Confusion table.
error.rate	Overall error ratio.
prior	Probability of classes.
type	Type of discriminant analysis.
validation	Type of validation.
num.class	Number of classes.
class.names	Class names.
method	Classification method.
num.correct	Number of correct observations.
results	Matrix with comparative classification results.

**Author(s)**

Paulo Cesar Ossani  
 Marcelo Angelo Cirillo

**References**

- Ferreira, D. F. *Estatística Multivariada*. 2a ed. revisada e ampliada. Lavras: Editora UFLA, 2011. 676 p.
- Mingoti, S. A. *Análise de dados através de métodos de estatística multivariada: uma abordagem aplicada*. Belo Horizonte: UFMG, 2005. 297 p.
- Rencher, A. C. *Methods of multivariate analysis*. 2th. ed. New York: J.Wiley, 2002. 708 p.
- Ripley, B. D. *Pattern Recognition and Neural Networks*. Cambridge University Press, 1996.
- Venables, W. N.; Ripley, B. D. *Modern Applied Statistics with S*. Fourth edition. Springer, 2002.

**Examples**

```
data(iris) # data set

data = iris[,1:4] # data to be classified
class = iris[,5] # data class
prior = c(1,1,1)/3 # a priori probability of the class

res <- DA(data, class, type = "lda", validation = "learning",
          method = "mle", prior = prior, testing = NA)

print("confusion table:"); res$confusion
print("Overall hit ratio:"); 1 - res$error.rate
print("Probability of classes:"); res$prior
print("classification method:"); res$method
print("type of discriminant analysis:"); res$type
print("class names:"); res$class.names
print("Number of classes:"); res$num.class
print("type of validation:"); res$validation
print("Number of correct observations:"); res$num.correct
print("Matrix with comparative classification results:"); res$results

### cross-validation ###
amostra = sample(2, nrow(data), replace = TRUE, prob = c(0.7,0.3))
datatrain = data[amostra == 1,] # training data
datatest = data[amostra == 2,] # test data

dim(datatrain) # training data dimension
dim(datatest) # test data dimension

testing = as.integer(rownames(datatest)) # test data index

res <- DA(data, class, type = "qda", validation = "testing",
          method = "moment", prior = NA, testing = testing)
```

```
print("confusion table:"); res$confusion
print("Overall hit ratio:"); 1 - res$error.rate
print("Number of correct observations:"); res$num.correct
print("Matrix with comparative classification results:"); res$results
```

---

DataCoffee

*Frequency data set.*


---

### Description

Set of data categorized by coffees, on sensorial abilities in the consumption of special coffees.

### Usage

```
data(DataCoffee)
```

### Format

Data set of a research done with the purpose of evaluating the concordance between the responses of different groups of consumers with different sensorial abilities. The experiment relates the sensorial analysis of special coffees defined by (A) Yellow Bourbon, cultivated at altitudes greater than 1200 m; (D) idem to (A) differing only in the preparation of the samples; (B) Acaia cultivated at an altitude of less than 1,100 m; (C) identical to (B) but differentiating the sample preparation. Here the data are categorized by coffees. The example given demonstrates the results found in OSSANI et al. (2017).

### References

Ossani, P. C.; Cirillo, M. A.; Borem, F. M.; Ribeiro, D. E.; Cortez, R. M.. Quality of specialty coffees: a sensory evaluation by consumers using the MFACT technique. *Revista Ciencia Agronomica (UFC. Online)*, v. 48, p. 92-100, 2017.

Ossani, P. C. *Qualidade de cafes especiais e nao especiais por meio da analise de multiplos fatores para tabelas de contingencias*. 2015. 107 p. Dissertacao (Mestrado em Estatistica e Experimentacao Agropecuaria) - Universidade Federal de Lavras, Lavras, 2015.

### Examples

```
data(DataCoffee) # categorized data set

data <- DataCoffee[,2:ncol(DataCoffee)]

rownames(data) <- as.character(t(DataCoffee[1:nrow(DataCoffee),1]))

group.names = c("Coffee A", "Coffee B", "Coffee C", "Coffee D")

mf <- MFA(data, c(16,16,16,16), c(rep("f",4)), group.names)
```

```
print("Principal components variances:"); round(mf$mtxA,2)

print("Matrix of the Partial Inertia / Score of the Variables:"); round(mf$mtxEV,2)

tit <- c("Scree-plot", "Individuals", "Individuals / Types coffees", "Inercias Groups")

Plot.MFA(mf, titles = tit, xlabel = NA, ylabel = NA,
         posleg = 2, boxleg = FALSE, color = TRUE,
         namarr = FALSE, linlab = NA, casc = FALSE) # plotting several graphs on the screen
```

---

DataFreq

*Frequency data set.*

---

### Description

Simulated data set with the weekly frequency of the number of coffee cups consumed weekly in some world capitals.

### Usage

```
data(DataFreq)
```

### Format

Set of data with 6 rows and 9 columns. There are 6 observations described by 9 variables: Group by sex and age, Sao Paulo - Cafe Bourbon, London - Cafe Bourbon, Athens - Cafe Bourbon, London - Cafe Acaia, Athens - Cafe Catuai, Sao Paulo - Cafe Catuai, Athens - Cafe Catuai.

### Author(s)

Paulo Cesar Ossani

Marcelo Angelo Cirillo

### Examples

```
data(DataFreq)
DataFreq
```

---

 DataInd

*Frequency data set.*


---

### Description

Set of data categorized by coffees, on sensorial abilities in the consumption of special coffees.

### Usage

```
data(DataInd)
```

### Format

Data set of a research done with the purpose of evaluating the concordance between the responses of different groups of consumers with different sensorial abilities. The experiment relates the sensorial analysis of special coffees defined by (A) Yellow Bourbon, cultivated at altitudes greater than 1200 m; (D) idem to (A) differing only in the preparation of the samples; (B) Acaia cultivated at an altitude of less than 1,100 m; (C) identical to (B) but differentiating the sample preparation. Here the data are categorized by coffees. The example given demonstrates the results found in OSSANI et al. (2017).

### References

Ossani, P. C.; Cirillo, M. A.; Borem, F. M.; Ribeiro, D. E.; Cortez, R. M.. Quality of specialty coffees: a sensory evaluation by consumers using the MFACT technique. *Revista Ciencia Agronomica (UFC. Online)*, v. 48, p. 92-100, 2017.

Ossani, P. C. *Qualidade de cafes especiais e nao especiais por meio da analise de multiplos fatores para tabelas de contingencias*. 2015. 107 p. Dissertacao (Mestrado em Estatistica e Experimentacao Agropecuaria) - Universidade Federal de Lavras, Lavras, 2015.

### Examples

```
data(DataInd) # categorized data set

data <- DataInd[,2:ncol(DataInd)]

rownames(data) <- as.character(t(DataInd[1:nrow(DataInd),1]))

group.names = c("Group 1", "Group 2", "Group 3", "Group 4")

mf <- MFA(data, c(16,16,16,16), c(rep("f",4)), group.names)

print("Principal components variances:"); round(mf$mtxA,2)

print("Matrix of the Partial Inertia / Score of the Variables:"); round(mf$mtxEV,2)

tit <- c("Scree-plot","Individuals","Individuals / Types coffees","Inercias Groups")
```

```
Plot.MFA(mf, titles = tit, xlabel = NA, ylabel = NA,  
         posleg = 2, boxleg = FALSE, color = TRUE,  
         namarr = FALSE, linlab = NA, casc = FALSE) # plotting several graphs on the screen
```

---

DataMix	<i>Mixed data set.</i>
---------	------------------------

---

**Description**

Simulated set of mixed data on consumption of coffee.

**Usage**

```
data(DataMix)
```

**Format**

Data set with 10 rows and 7 columns. Being 10 observations described by 7 variables: Cooperatives/Tasters, Average grades given to analyzed coffees, Years of work as a taster, Taster with technical training, Taster exclusively dedicated, Average frequency of the coffees Classified as special, Average frequency of the coffees as commercial.

**Author(s)**

Paulo Cesar Ossani  
Marcelo Angelo Cirillo

**Examples**

```
data(DataMix)  
DataMix
```

---

DataQuali	<i>Qualitative data set</i>
-----------	-----------------------------

---

**Description**

Set simulated of qualitative data on consumption of coffee.

**Usage**

```
data(DataQuali)
```

**Format**

Data set simulated with 12 rows and 6 columns. Being 12 observations described by 6 variables: Sex, Age, Smoker, Marital status, Sportsman, Study.

**Author(s)**

Paulo Cesar Ossani

Marcelo Angelo Cirillo

**Examples**

```
data(DataQuali)
DataQuali
```

---

DataQuan

*Quantitative data set*

---

**Description**

Set simulated of quantitative data on grades given to some sensory characteristics of coffees.

**Usage**

```
data(DataQuan)
```

**Format**

Data set with 6 rows and 11 columns. Being 6 observations described by 11 variables: Coffee, Chocolate, Caramelised, Ripe, Sweet, Delicate, Nutty, Caramelised, Chocolate, Spicy, Caramelised.

**Author(s)**

Paulo Cesar Ossani

Marcelo Angelo Cirillo

**Examples**

```
data(DataQuan)
DataQuan
```

---

FA *Factor Analysis (FA).*

---

### Description

Performs factorial analysis (FA) in a data set.

### Usage

```
FA(data, method = "PC", type = 2, nfactor = 1, rotation = "None",
  scoresobs = "Bartlett", converg = 1e-5, iteracao = 1000,
  testfit = TRUE)
```

### Arguments

data	Data to be analyzed.
method	Method of analysis: "PC" - Principal Components (default), "PF" - Principal Factor, "ML" - Maximum Likelihood.
type	1 for analysis using the covariance matrix, 2 for analysis using the correlation matrix (default).
rotation	Type of rotation: "None" (default), "Varimax" and "Promax".
nfactor	Number of factors (default = 1).
scoresobs	Type of scores for the observations: "Bartlett" (default) or "Regression".
converg	Limit value for convergence to sum of the squares of the residuals for Maximum likelihood method (default = 1e-5).
iteracao	Maximum number of iterations for Maximum Likelihood method (default = 1000).
testfit	Tests the model fit to the method of Maximum Likelihood (default = TRUE).

### Value

mtxMC	Matrix of correlation / covariance.
mtxAutv1r	Matrix of eigenvalues.
mtxAutvec	Matrix of eigenvectors.
mtxvar	Matrix of variances and proportions.
mtxcarga	Matrix of factor loadings.
mtxvaresp	Matrix of specific variances.
mtxcomuna	Matrix of commonalities.
mtxresidue	Matrix of residues.
v1rsqrs	Upper limit value for sum of squares of the residues.

vlsqr	Sum of squares of the residues.
mtxresult	Matrix with all associated results.
mtxscores	Matrix with scores of the observations.
coefscores	Matrix with the scores of the coefficients of the factors.

**Author(s)**

Paulo Cesar Ossani  
 Marcelo Angelo Cirillo

**References**

- Mingot, S. A. *Análise de dados através de métodos de estatística multivariada: uma abordagem aplicada*. Belo Horizonte: UFMG, 2005. 297 p.
- Kaiser, H. F. *The varimax criterion for analytic rotation in factor analysis*. *Psychometrika* 23, 187-200, 1958.
- Rencher, A. C. *Methods of multivariate analysis*. 2th. ed. New York: J.Wiley, 2002. 708 p.
- Ferreira, D. F. *Estatística Multivariada*. 2a ed. revisada e ampliada. Lavras: Editora UFLA, 2011. 676 p.

**See Also**

[Plot.FA](#)

**Examples**

```
data(DataQuan) # data set

data <- DataQuan[,2:ncol(DataQuan)]

rownames(data) <- DataQuan[,1]

res <- FA(data, method = "PC", type = 2, nfactor = 3, rotation = "None",
          scoresobs = "Bartlett", converg = 1e-5, iteracao = 1000,
          testfit = TRUE)

print("Matrix with all associated results:"); round(res$mtxresult,3)

print("Sum of squares of the residues:"); round(res$vlsqr,3)

print("Matrix of the factor loadings.:"); round(res$mtxcarga,3)

print("Matrix with scores of the observations:"); round(res$mtxscores,3)

print("Matrix with the scores of the coefficients of the factors:"); round(res$coefscores,3)
```

GrandTour

*Animation technique Grand Tour.***Description**

Performs the exploration of the data through the technique of animation Grand Tour.

**Usage**

```
GrandTour(data, method = "Interpolation", title = NA, xlabel = NA,
          ylabel = NA, size = 1.1, grid = TRUE, color = TRUE, linlab = NA,
          class = NA, classcolor = NA, posleg = 2, boxleg = TRUE,
          axesvar = TRUE, axes = TRUE, numrot = 200, choicerot = NA,
          savptc = FALSE, width = 3236, height = 2000, res = 300)
```

**Arguments**

data	Numerical data set.
method	Method used for rotations: "Interpolation" - Interpolation method (default), "Torus" - Torus method, "Pseudo" - Pseudo Grand Tour method.
title	Titles of the graphics, if not set, assumes the default text.
xlabel	Names the X axis, if not set, assumes the default text.
ylabel	Names the Y axis, if not set, assumes the default text.
size	Size of the points in the graphs.
grid	Put grid on graphs (default = TRUE).
color	Colored graphics (default = TRUE).
linlab	Vector with the labels for the observations.
class	Vector with names of data classes.
classcolor	Vector with the colors of the classes.
posleg	0 with no caption, 1 for caption in the left upper corner, 2 for caption in the right upper corner (default), 3 for caption in the right lower corner, 4 for caption in the left lower corner.
boxleg	Puts the frame in the caption (default = TRUE).
axesvar	Puts axes of rotation of the variables (default = TRUE).
axes	Plots the X and Y axes (default = TRUE).
numrot	Number of rotations (default = 200). If method = "Interpolation", numrot represents the angle of rotation.

choicerot	Choose specific rotation and display on the screen, or save the image if savptc = TRUE.
savptc	Saves graphics images to files (default = FALSE).
width	Graphics images width when savptc = TRUE (default = 3236).
height	Graphics images height when savptc = TRUE (default = 2000).
res	Nominal resolution in ppi of the graphics images when savptc = TRUE (default = 300).

**Value**

Graphs with rotations.

proj.data	Projected data.
vector.opt	Vector projection.
method	method used on Grand Tour.

**Author(s)**

Paulo Cesar Ossani  
 Marcelo Angelo Cirillo

**References**

- Asimov, D. The Grand Tour: A Tool for Viewing Multidimensional data. *SIAM Journal of Scientific and Statistical Computing*, 6(1), 128-143, 1985.
- Asimov, D.; Buja, A. The grand tour via geodesic interpolation of 2-frames. in Visual data Exploration and Analysis. *Symposium on Electronic Imaging Science and Technology*, IS&T/SPIE. 1994.
- Buja, A.; Asimov, D. Grand tour methods: An outline. *Computer Science and Statistics*, 17:63-67. 1986.
- Buja, A.; Cook, D.; Asimov, D.; Hurley, C. Computational methods for High-Dimensional Rotations in data Visualization, in C. R. Rao, E. J. Wegman & J. L. Solka, eds, "*Handbook of Statistics: data Mining and Visualization*", Elsevier/North Holland, <http://www.elsevier.com>, pp. 391-413. 2005.
- Hurley, C.; Buja, A. Analyzing high-dimensional data with motion graphics, *SIAM Journal of Scientific and Statistical Computing*, 11 (6), 1193-1211. 1990.
- Martinez, W. L.; Martinez, A. R.; Solka, J.; *Exploratory data Analysis with MATLAB*, 2th. ed. New York: Chapman & Hall/CRC, 2010. 499 p.
- Young, F. W.; Rheingans P. Visualizing structure in high-dimensional multivariate data, *IBM Journal of Research and Development*, 35:97-107, 1991.
- Young, F. W.; Faldowski R. A.; McFarlane M. M. *Multivariate statistical visualization*, in *Handbook of Statistics*, Vol 9, C. R. Rao (ed.), The Netherlands: Elsevier Science Publishers, 959-998, 1993.

**Examples**

```

data(iris) # database

res <- GrandTour(iris[,1:4], method = "Torus", title = NA, xlabel = NA, ylabel = NA,
  color = TRUE, linlab = NA, class = NA, posleg = 2, boxleg = TRUE,
  axesvar = TRUE, axes = FALSE, numrot = 10, choicerot = NA,
  savptc = FALSE, width = 3236, height = 2000, res = 300)

print("Projected data:"); res$proj.data
print("Projection vectors:"); res$vector.opt
print("Grand Tour projection method:"); res$method

res <- GrandTour(iris[,1:4], method = "Interpolation", title = NA, xlabel = NA, ylabel = NA,
  color = TRUE, linlab = NA, posleg = 2, boxleg = FALSE, axesvar = FALSE,
  axes = FALSE, numrot = 10, choicerot = NA, class = iris[,5],
  classcolor = c("goldenrod3", "gray53", "red"), savptc = FALSE,
  width = 3236, height = 2000, res = 300)

print("Projected data:"); res$proj.data
print("Projection vectors:"); res$vector.opt
print("Grand Tour projection method:"); res$method

```

---

 GSVD

*Generalized Singular Value Decomposition (GSVD).*


---

**Description**

Given the matrix  $A$  of order  $n \times m$ , the generalized singular value decomposition (GSVD) involves the use of two sets of positive square matrices of order  $n \times n$  and  $m \times m$  respectively. These two matrices express constraints imposed, respectively, on the lines and columns of  $A$ .

**Usage**

```
GSVD(data, plin = NULL, pcol = NULL)
```

**Arguments**

<code>data</code>	Matrix used for decomposition.
<code>plin</code>	Weight for rows.
<code>pcol</code>	Weight for columns

**Details**

If `plin` or `pcol` is not used, it will be calculated as the usual singular value decomposition.

**Value**

d	Eigenvalues, that is, line vector with singular values of the decomposition.
u	Eigenvectors referring rows.
v	Eigenvectors referring columns.

**Author(s)**

Paulo Cesar Ossani  
 Marcelo Angelo Cirillo

**References**

Abdi, H. Singular Value Decomposition (SVD) and Generalized Singular Value Decomposition (GSVD). In: SALKIND, N. J. (Ed.). *Encyclopedia of measurement and statistics*. Thousand Oaks: Sage, 2007. p. 907-912.

**Examples**

```
data <- matrix(c(1,2,3,4,5,6,7,8,9,10,11,12), nrow = 4, ncol = 3)

svd(data) # Usual Singular Value Decomposition

GSVD(data) # GSVD with the same previous results

# GSVD with weights for rows and columns
GSVD(data, plin = c(0.1,0.5,2,1.5), pcol = c(1.3,2,0.8))
```

---

IM	<i>Indicator matrix.</i>
----	--------------------------

---

**Description**

In the indicator matrix the elements are arranged in the form of *dummy* variables, in other words, 1 for a category chosen as a response variable and 0 for the other categories of the same variable.

**Usage**

```
IM(data, names = TRUE)
```

**Arguments**

data	Categorical data.
names	Include the names of the variables in the levels of the Indicator Matrix (default = TRUE).

**Value**

mtxIndc	Returns converted data in the indicator matrix.
---------	---

**Author(s)**

Paulo Cesar Ossani  
 Marcelo Angelo Cirillo

**References**

Rencher, A. C. *Methods of multivariate analysis*. 2th. ed. New York: J.Wiley, 2002. 708 p.

**Examples**

```
data <- matrix(c("S","S","N","N",1,2,3,4,"N","S","T","N"), nrow = 4, ncol = 3)
IM(data, names = FALSE)
data(DataQuali) # qualitative data set
IM(DataQuali, names = TRUE)
```

---

 LocLab

---

*Function for better position of the labels in the graphs.*


---

**Description**

Function for better position of the labels in the graphs.

**Usage**

```
LocLab(x, y = NULL, labels = seq(along = x), cex = 1,
       method = c("SANN", "GA"), allowSmallOverlap = FALSE,
       trace = FALSE, shadotext = FALSE,
       doPlot = TRUE, ...)
```

**Arguments**

x	Coordinate x
y	Coordinate y
labels	The labels
cex	cex
method	Not used
allowSmallOverlap	Boolean
trace	Boolean
shadotext	Boolean
doPlot	Boolean
...	Other arguments passed to or from other methods

**Value**

See the text of the function.

---

MDS

*Multidimensional Scaling (MDS).*


---

**Description**

Performs Multidimensional Scaling (MDS) on a data set.

**Usage**

```
MDS(data, distance = "euclidean", title = NA, xlabel = NA,
     ylabel = NA, posleg = 2, boxleg = TRUE, axes = TRUE,
     size = 1.1, grid = TRUE, color = TRUE, linlab = NA,
     class = NA, classcolor = NA, savptc = FALSE, width = 3236,
     height = 2000, res = 300)
```

**Arguments**

data	Data to be analyzed.
distance	Metric of the distance: "euclidean" (default), "maximum", "manhattan", "canberra", "binary" or "minkowski".
title	Titles of the graphics, if not set, assumes the default text.
xlabel	Names the X axis, if not set, assumes the default text.
ylabel	Names the Y axis, if not set, assumes the default text.
posleg	0 with no caption, 1 for caption in the left upper corner, 2 for caption in the right upper corner (default), 3 for caption in the right lower corner, 4 for caption in the left lower corner.
boxleg	Puts the frame in the caption (default = TRUE).
axes	Plot the X and Y axes (default = TRUE).
size	Size of the points in the graphs.
grid	Put grid on graphs (default = TRUE).
color	Colored graphics (default = TRUE).
linlab	Vector with the labels for the observations.
class	Vector with names of data classes.
classcolor	Vector with the colors of the classes.
savptc	Saves graphics images to files (default = FALSE).
width	Graphics images width when savptc = TRUE (default = 3236).
height	Graphics images height when savptc = TRUE (default = 2000).
res	Nominal resolution in ppi of the graphics images when savptc = TRUE (default = 300).

**Value**

Multidimensional Scaling.

mtxD                Matrix of the distances.

**Author(s)**

Paulo Cesar Ossani

Marcelo Angelo Cirillo

**References**

Mingoti, S. A. *Analise de dados atraves de metodos de estatistica multivariada: uma abordagem aplicada*. Belo Horizonte: UFMG, 2005. 297 p.

Rencher, A. C. *Methods of multivariate analysis*. 2th. ed. New York: J.Wiley, 2002. 708 p.

**Examples**

```
data(iris) # data set

data <- iris[,1:4]

cls <- iris[,5] # data class

md <- MDS(data = data, distance = "euclidean", title = NA, xlabel = NA,
          ylabel = NA, posleg = 2, boxleg = TRUE, axes = TRUE, color = TRUE,
          linlab = NA, class = cls, classcolor = c("goldenrod3", "gray53", "red"),
          savptc = FALSE, width = 3236, height = 2000, res = 300)

print("Matrix of the distances:"); md$mtxD
```

---

MFA

*Multiple Factor Analysis (MFA).*

---

**Description**

Perform Multiple Factor Analysis (MFA) on groups of variables. The groups of variables can be quantitative, qualitative, frequency (MFACT) data, or mixed data.

**Usage**

```
MFA(data, groups, typegroups = rep("n",length(groups)), namegroups = NULL)
```

**Arguments**

data	Data to be analyzed.
groups	Number of columns for each group in order following the order of data in 'data'.
typegroups	Type of group: "n" for numerical data (default), "c" for categorical data, "f" for frequency data.
namegroups	Names for each group.

**Value**

vtrG	Vector with the sizes of each group.
vtrNG	Vector with the names of each group.
vtrplin	Vector with the values used to balance the lines of the Z matrix.
vtrpcol	Vector with the values used to balance the columns of the Z matrix.
mtxZ	Matrix concatenated and balanced.
mtxA	Matrix of the eigenvalues (variances) with the proportions and proportions accumulated.
mtxU	Matrix U of the singular decomposition of the matrix Z.
mtxV	Matrix V of the singular decomposition of the matrix Z.
mtxF	Matrix global factor scores where the lines are the observations and the columns the components.
mtxEFG	Matrix of the factor scores by group.
mtxCCP	Matrix of the correlation of the principal components with original variables.
mtxEV	Matrix of the partial inertias / scores of the variables

**Author(s)**

Paulo Cesar Ossani  
Marcelo Angelo Cirillo

**References**

- Abdessemed, L.; Escofier, B. Analyse factorielle multiple de tableaux de frequences: comparaison avec l'analyse canonique des correspondences. *Journal de la Societe de Statistique de Paris*, Paris, v. 137, n. 2, p. 3-18, 1996..
- Abdi, H. Singular Value Decomposition (SVD) and Generalized Singular Value Decomposition (GSVD). In: SALKIND, N. J. (Ed.). *Encyclopedia of measurement and statistics*. Thousand Oaks: Sage, 2007. p. 907-912.
- Abdi, H.; Valentin, D. Multiple factor analysis (MFA). In: SALKIND, N. J. (Ed.). *Encyclopedia of measurement and statistics*. Thousand Oaks: Sage, 2007. p. 657-663.
- Abdi, H.; Williams, L. Principal component analysis. *WIREs Computational Statistics*, New York, v. 2, n. 4, p. 433-459, July/Aug. 2010.

- Abdi, H.; Williams, L.; Valentin, D. Multiple factor analysis: principal component analysis for multitable and multiblock data sets. *WIREs Computational Statistics*, New York, v. 5, n. 2, p. 149-179, Feb. 2013.
- Becue-Bertaut, M.; Pages, J. A principal axes method for comparing contingency tables: MFACT. *Computational Statistics & data Analysis*, New York, v. 45, n. 3, p. 481-503, Feb. 2004
- Becue-Bertaut, M.; Pages, J. Multiple factor analysis and clustering of a mixture of quantitative, categorical and frequency data. *Computational Statistics & data Analysis*, New York, v. 52, n. 6, p. 3255-3268, Feb. 2008.
- Bezecri, J. Analyse de l'inertie intraclasse par l'analyse d'un tableau de contingence: intra-classinertia analysis through the analysis of a contingency table. *Les Cahiers de l'Analyse des Donnees*, Paris, v. 8, n. 3, p. 351-358, 1983.
- Escofier, B. Analyse factorielle en reference a un modele: application a l'analyse d'un tableau d'echanges. *Revue de Statistique Appliquee*, Paris, v. 32, n. 4, p. 25-36, 1984.
- Escofier, B.; Drouet, D. Analyse des differences entre plusieurs tableaux de frequence. *Les Cahiers de l'Analyse des Donnees*, Paris, v. 8, n. 4, p. 491-499, 1983.
- Escofier, B.; Pages, J. *Analyse factorielles simples et multiples*. Paris: Dunod, 1990. 267 p.
- Escofier, B.; Pages, J. *Analyses factorielles simples et multiples: objectifs, methodes et interpretation*. 4th ed. Paris: Dunod, 2008. 318 p.
- Escofier, B.; Pages, J. *Comparaison de groupes de variables definies sur le meme ensemble d'individus: un exemple d'applications*. Le Chesnay: Institut National de Recherche en Informatique et en Automatique, 1982. 121 p.
- Escofier, B.; Pages, J. Multiple factor analysis (AFUMULT package). *Computational Statistics & data Analysis*, New York, v. 18, n. 1, p. 121-140, Aug. 1994
- Greenacre, M.; Blasius, J. *Multiple correspondence analysis and related methods*. New York: Taylor and Francis, 2006. 607 p.
- Ossani, P. C.; Cirillo, M. A.; Borem, F. M.; Ribeiro, D. E.; Cortez, R. M. Quality of specialty coffees: a sensory evaluation by consumers using the MFACT technique. *Revista Ciencia Agronomica (UFC. Online)*, v. 48, p. 92-100, 2017.
- Pages, J. Analyse factorielle multiple appliquee aux variables qualitatives et aux donnees mixtes. *Revue de Statistique Appliquee*, Paris, v. 50, n. 4, p. 5-37, 2002.
- Pages, J.. Multiple factor analysis: main features and application to sensory data. *Revista Colombiana de Estadistica*, Bogota, v. 27, n. 1, p. 1-26, 2004.

## See Also

[Plot.MFA](#)

## Examples

```
data(DataMix) # mixed dataset

data <- DataMix[,2:ncol(DataMix)]

rownames(data) <- DataMix[1:nrow(DataMix),1]
```

```
group.names = c("Grade Cafes/Work", "Formation/Dedication", "Coffees")  
mf <- MFA(data = data, c(2,2,2), typegroups = c("n","c","f"), group.names) # performs MFA  
print("Principal Component Variances:"); round(mf$mtxA,2)  
print("Matrix of the Partial Inertia / Score of the Variables:"); round(mf$mtxEV,2)
```

---

NormData

*Normalizes the data.*

---

### Description

Function that normalizes the data globally, or by column.

### Usage

```
NormData(data, type = 1)
```

### Arguments

data	Data to be analyzed.
type	1 normalizes overall (default), 2 normalizes per column.

### Value

dataNorm	Normalized data.
----------	------------------

### Author(s)

Paulo Cesar Ossani  
Marcelo Angelo Cirillo

### Examples

```
data(DataQuan) # set of quantitative data  
data <- DataQuan[,2:8]  
res <- NormData(data, type = 1) # normalizes the data globally  
res # Globally standardized data  
sd(res) # overall standard deviation  
mean(res) # overall mean
```

```
res <- NormData(data, type = 2) # normalizes the data per column  
res # standardized data per column  
apply(res, 2, sd) # standard deviation per column  
colMeans(res) # column averages
```

---

NormTest	<i>Test of normality of the data.</i>
----------	---------------------------------------

---

### Description

Check the normality of the data, based on the asymmetry coefficient test.

### Usage

```
NormTest(data, sign = 0.05)
```

### Arguments

data	Data to be analyzed.
sign	Test significance level (default 5%).

### Value

statistic	Observed Chi-square value, that is, the test statistic.
chisquare	Chi-square value calculated.
gl	Degree of freedom.
p.value	p-value.

### Author(s)

Paulo Cesar Ossani  
Marcelo Angelo Cirillo

### References

Mingoti, S. A. *Análise de dados através de métodos de estatística multivariada: uma abordagem aplicada*. Belo Horizonte: UFMG, 2005. 297 p.

Rencher, A. C. *Methods of Multivariate Analysis*. 2th. ed. New York: J.Wiley, 2002. 708 p.

Ferreira, D. F. *Estatística Multivariada*. 2a ed. revisada e ampliada. Lavras: Editora UFLA, 2011. 676 p.

**Examples**

```
data <- cbind(rnorm(100,2,3), rnorm(100,1,2))

NormTest(data)

plot(density(data))

data <- cbind(rexp(200,3), rexp(200,3))

NormTest(data, sign = 0.01)

plot(density(data))
```

---

PCA

*Principal Components Analysis (PCA).*

---

**Description**

Performs principal component analysis (PCA) in a data set.

**Usage**

```
PCA(data, type = 1)
```

**Arguments**

data	Data to be analyzed.
type	1 for analysis using the covariance matrix (default), 2 for analysis using the correlation matrix.

**Value**

mtxC	Matrix of covariance or correlation according to "type".
mtxAutv1r	Matrix of eigenvalues (variances) with the proportions and proportions accumulated.
mtxAutvec	Matrix of eigenvectors - principal components.
mtxVCP	Matrix of covariance of the principal components with the original variables.
mtxCCP	Matrix of correlation of the principal components with the original variables.
mtxscores	Matrix with scores of the principal components.
mtxresult	Matrix with all associated results.

**Author(s)**

Paulo Cesar Ossani  
Marcelo Angelo Cirillo

## References

Hotelling, H. Analysis of a complex of statistical variables into principal components. *Journal of Educational Psychology*, Arlington, v. 24, p. 417-441, Sept. 1933.

Mingoti, S. A. *Analise de dados atraves de metodos de estatistica multivariada: uma abordagem aplicada*. Belo Horizonte: UFMG, 2005. 297 p.

Ferreira, D. F. *Estatistica Multivariada*. 2a ed. revisada e ampliada. Lavras: Editora UFLA, 2011. 676 p.

Rencher, A. C. *Methods of multivariate analysis*. 2th. ed. New York: J.Wiley, 2002. 708 p.

## See Also

[Plot.PCA](#)

## Examples

```
data(DataQuan) # set of quantitative data

data <- DataQuan[,2:8]

rownames(data) <- DataQuan[1:nrow(DataQuan),1]

pc <- PCA(data, type = 1) # performs the PCA

print("Covariance matrix / Correlation:"); round(pc$mtxC,2)

print("Principal Components:"); round(pc$mtxAutvec,2)

print("Principal Component Variances:"); round(pc$mtxAutvlr,2)

print("Covariance of the Principal Components:"); round(pc$mtxVCP,2)

print("Correlation of the Principal Components:"); round(pc$mtxCCP,2)

print("Scores of the Principal Components:"); round(pc$mtxscores,2)

print("Matrix with all associated results:"); round(pc$mtxresult,3)
```

---

Plot.CA

*Graphs of the simple (CA) and multiple correspondence analysis (MCA).*

---

## Description

Graphs of the simple (CA) and multiple correspondence analysis (MCA).

**Usage**

```
Plot.CA(CA, titles = NA, xlabel = NA, ylabel = NA, size = 1.1,
        grid = TRUE, color = TRUE, linlab = NA, axes = TRUE,
        savptc = FALSE, width = 3236, height = 2000, res = 300,
        casc = TRUE)
```

**Arguments**

CA	Data of the CA function.
titles	Titles of the graphics, if not set, assumes the default text..
xlabel	Names the X axis, if not set, assumes the default text.
ylabel	Names the Y axis, if not set, assumes the default text.
size	Size of the points in the graphs.
grid	Put grid on graphs (default = TRUE).
color	Colored graphics (default = TRUE).
linlab	Vector with the labels for the observations.
axes	Plots the X and Y axes (default = TRUE).
savptc	Saves graphics images to files (default = FALSE).
width	Graphics images width when savptc = TRUE (default = 3236).
height	Graphics images height when savptc = TRUE (default = 2000).
res	Nominal resolution in ppi of the graphics images when savptc = TRUE (default = 300).
casc	Cascade effect in the presentation of the graphics (default = TRUE).

**Value**

Returns several graphs.

**Author(s)**

Paulo Cesar Ossani  
 Marcelo Angelo Cirillo

**See Also**

[CA](#)

**Examples**

```
data(DataFreq) # frequency data set

data <- DataFreq[,2:ncol(DataFreq)]

rownames(data) <- DataFreq[1:nrow(DataFreq),1]
```

```

res <- CA(data, "f") # performs CA

tit <- c("Scree-plot", "Observations", "Variables", "Observations / Variables")

Plot.CA(res, titles = tit, xlabel = NA, ylabel = NA, axes = TRUE,
        color = TRUE, linlab = rownames(data), savptc = FALSE,
        width = 3236, height = 2000, res = 300, casc = FALSE)

data(DataQuali) # qualitative data set

data <- DataQuali[,2:ncol(DataQuali)]

res <- CA(data, "c", "b") # performs CA

tit <- c("", "", "Graph of the variables")

Plot.CA(res, titles = tit, xlabel = NA, ylabel = NA,
        color = TRUE, linlab = NA, savptc = FALSE,
        width = 3236, height = 2000, res = 300,
        axes = TRUE, casc = FALSE)

```

---

Plot.CCA

*Graphs of the Canonical Correlation Analysis (CCA).*


---

### Description

Graphs of the Canonical Correlation Analysis (CCA).

### Usage

```

Plot.CCA(CCA, titles = NA, xlabel = NA, ylabel = NA, size = 1.1,
        grid = TRUE, color = TRUE, axes = TRUE, savptc = FALSE,
        width = 3236, height = 2000, res = 300, casc = TRUE)

```

### Arguments

CCA	Data of the CCA function.
titles	Titles of the graphics, if not set, assumes the default text.
xlabel	Names the X axis, if not set, assumes the default text.
ylabel	Names the Y axis, if not set, assumes the default text.
size	Size of the points in the graphs.
grid	Put grid on graphs (default = TRUE).
color	Colored graphics (default = TRUE).
axes	Plots the X and Y axes (default = TRUE).

savptc	Saves graphics images to files (default = FALSE).
width	Graphics images width when savptc = TRUE (default = 3236).
height	Graphics images height when savptc = TRUE (default = 2000).
res	Nominal resolution in ppi of the graphics images when savptc = TRUE (default = 300).
cas	Cascade effect in the presentation of the graphics (default = TRUE).

**Value**

Returns several graphs.

**Author(s)**

Paulo Cesar Ossani

Marcelo Angelo Cirillo

**See Also**

[CCA](#)

**Examples**

```
data(DataMix) # database

data <- DataMix[,2:ncol(DataMix)]

rownames(data) <- DataMix[,1]

X <- data[,1:2]

Y <- data[,5:6]

res <- CCA(X, Y, type = 2, test = "Bartlett", sign = 0.05) # performs CCA

tit <- c("Scree-plot", "Correlations", "Scores of the group X", "Scores of the group Y")

Plot.CCA(res, titles = tit, xlabel = NA, ylabel = NA,
         color = TRUE, savptc = FALSE, width = 3236,
         height = 2000, res = 300, axes = TRUE,
         cas = FALSE)
```

---

`Plot.CI`*Graph of Univariate and Multivariate Confidence Intervals.*

---

**Description**

Graph of Univariate and Multivariate Confidence Intervals.

**Usage**

```
Plot.CI(ci, title = NA, xlabel = NA, ylabel = NA, size = 0.9,  
        grid = TRUE, color = TRUE, savptc = FALSE, width = 3236,  
        height = 2000, res = 300, casc = FALSE)
```

**Arguments**

<code>ci</code>	Data from the CI function, or with the same structure.
<code>title</code>	Plot title; if not specified, default text is used.
<code>xlabel</code>	X-axis label; if not specified, default text is used.
<code>ylabel</code>	Y-axis label; if not specified, default text is used.
<code>size</code>	Point size in the plot.
<code>grid</code>	Adds a grid to the plot (default = TRUE).
<code>color</code>	Colored plot (default = TRUE).
<code>savptc</code>	Saves graphics images to files (default = FALSE).
<code>width</code>	Graphics images width when <code>savptc = TRUE</code> (default = 3236).
<code>height</code>	Graphics images height when <code>savptc = TRUE</code> (default = 2000).
<code>res</code>	Nominal resolution in ppi of the graphics images when <code>savptc = TRUE</code> (default = 300).
<code>casc</code>	Cascade effect in the presentation of the graphics (default = FALSE).

**Value**

Returns plot.

**Author(s)**

Paulo Cesar Ossani

**See Also**

[CI](#)

**Examples**

```

data(iris) # data set

res <- CI(data = iris[,1:4], sigma = NA, conf = 0.95, type = "T")

tit <- "Univariate Confidence Interval"

Plot.CI(ci = res$ciu$CIu, title = tit, xlabel = NA, ylabel = '',
        size = 1, grid = TRUE, color = TRUE, savptc = FALSE,
        width = 3236, height = 2000, res = 300, casc = FALSE)

tit <- "Multivariate Confidence Interval"

Plot.CI(ci = res$cim$CIu, title = tit, xlabel = NA, ylabel = '',
        size = 1, grid = TRUE, color = TRUE, savptc = FALSE,
        width = 3236, height = 2000, res = 300, casc = FALSE)

```

---

Plot.Cor

*Plot of correlations between variables.*


---

**Description**

It performs the correlations between the variables of a database and presents it in graph form.

**Usage**

```

Plot.Cor(data, title = NA, grid = TRUE, leg = TRUE, boxleg = FALSE,
         text = FALSE, arrow = TRUE, color = TRUE, namesvar = NA,
         savptc = FALSE, width = 3236, height = 2000, res = 300)

```

**Arguments**

data	Numeric data set.
title	Title for the plot, if not defined it assumes standard text.
grid	Puts grid on plot (default = TRUE).
leg	Put the legend on the plot (default = TRUE)
boxleg	Put frame in the legend (default = FALSE).
text	Puts correlation values in circles (default = FALSE).
arrow	Positive (up) and negative (down) correlation arrows (default = TRUE).
color	Colorful plot (default = TRUE).
namesvar	Vector with the variable names, if omitted it assumes the names in 'date'.
savptc	Saves graphics images to files (default = FALSE).
width	Graphics images width when savptc = TRUE (default = 3236).

height Graphics images height when savptc = TRUE (default = 2000).  
 res Nominal resolution in ppi of the graphics images when savptc = TRUE (default = 300).

**Value**

Plot with the correlations between the variables in 'date'.

**Author(s)**

Paulo Cesar Ossani

**Examples**

```
data(iris) # data set
```

```
Plot.Cor(data = iris[,1:4], title = NA, grid = TRUE, leg = TRUE, boxleg = FALSE,
          text = FALSE, arrow = TRUE, color = TRUE, namesvar = NA, savptc = FALSE,
          width = 3236, height = 2000, res = 300)
```

```
Plot.Cor(data = iris[,1:4], title = NA, grid = TRUE, leg = TRUE, boxleg = FALSE,
          text = TRUE, arrow = TRUE, color = TRUE, namesvar = c("A1", "B2", "C3", "D4"),
          savptc = FALSE, width = 3236, height = 2000, res = 300)
```

---

 Plot.FA

---

*Graphs of the Factorial Analysis (FA).*


---

**Description**

Graphs of the Factorial Analysis (FA).

**Usage**

```
Plot.FA(FA, titles = NA, xlabel = NA, ylabel = NA, size = 1.1,
        grid = TRUE, color = TRUE, linlab = NA, axes = TRUE, class = NA,
        classcolor = NA, posleg = 2, boxleg = TRUE, savptc = FALSE,
        width = 3236, height = 2000, res = 300, casc = TRUE)
```

**Arguments**

FA Data of the FA function.  
 titles Titles of the graphics, if not set, assumes the default text.  
 xlabel Names the X axis, if not set, assumes the default text.  
 ylabel Names the Y axis, if not set, assumes the default text.  
 size Size of the points in the graphs.  
 grid Put grid on graphs (default = TRUE).

color	Colored graphics (default = TRUE).
linlab	Vector with the labels for the observations.
axes	Plots the X and Y axes (default = TRUE).
class	Vector with names of data classes.
classcolor	Vector with the colors of the classes.
posleg	0 with no caption, 1 for caption in the left upper corner, 2 for caption in the right upper corner (default), 3 for caption in the right lower corner, 4 for caption in the left lower corner.
boxleg	Puts the frame in the caption (default = TRUE).
savptc	Saves graphics images to files (default = FALSE).
width	Graphics images width when savptc = TRUE (default = 3236).
height	Graphics images height when savptc = TRUE (default = 2000).
res	Nominal resolution in ppi of the graphics images when savptc = TRUE (default = 300).
casc	Cascade effect in the presentation of the graphics (default = TRUE).

**Value**

Returns several graphs.

**Author(s)**

Paulo Cesar Ossani  
Marcelo Angelo Cirillo

**See Also**

[FA](#)

**Examples**

```
data(iris) # conjunto de dados

data <- iris[,1:4]

cls <- iris[,5] # classe dos dados

res <- FA(data, method = "PC", type = 2, nfactor = 3)

tit <- c("Scree-plot", "Scores of the Observations", "Factorial Loadings", "Biplot")

cls <- as.character(iris[,5])

Plot.FA(FA = res, titles = tit, xlabel = NA, ylabel = NA,
        color = TRUE, linlab = NA, savptc = FALSE, size = 1.1,
```

```
posleg = 1, boxleg = FALSE, class = cls, axes = TRUE,
classcolor = c("blue3", "red", "goldenrod3"),
width = 3236, height = 2000, res = 300, casc = FALSE)
```

---

Plot.MFA

*Graphics of the Multiple Factor Analysis (MFA).*


---

### Description

Graphics of the Multiple Factor Analysis (MFA).

### Usage

```
Plot.MFA(MFA, titles = NA, xlabel = NA, ylabel = NA,
posleg = 2, boxleg = TRUE, size = 1.1, grid = TRUE,
color = TRUE, groupcolor = NA, namarr = FALSE,
linlab = NA, savptc = FALSE, width = 3236,
height = 2000, res = 300, casc = TRUE)
```

### Arguments

MFA	Data of the MFA function.
titles	Titles of the graphics, if not set, assumes the default text.
xlabel	Names the X axis, if not set, assumes the default text.
ylabel	Names the Y axis, if not set, assumes the default text.
posleg	1 for caption in the left upper corner, 2 for caption in the right upper corner (default), 3 for caption in the right lower corner, 4 for caption in the left lower corner.
boxleg	Puts frame in legend (default = TRUE).
size	Size of the points in the graphs.
grid	Put grid on graphs (default = TRUE).
color	Colored graphics (default = TRUE).
groupcolor	Vector with the colors of the groups.
namarr	Puts the points names in the cloud around the centroid in the graph corresponding to the global analysis of the Individuals and Variables (default = FALSE).
linlab	Vector with the labels for the observations, if not set, assumes the default text.
savptc	Saves graphics images to files (default = FALSE).
width	Graphics images width when savptc = TRUE (default = 3236).
height	Graphics images height when savptc = TRUE (default = 2000).
res	Nominal resolution in ppi of the graphics images when savptc = TRUE (default = 300).
casc	Cascade effect in the presentation of the graphics (default = TRUE).

**Value**

Returns several graphs.

**Author(s)**

Paulo Cesar Ossani

Marcelo Angelo Cirillo

**See Also**

[MFA](#)

**Examples**

```
data(DataMix) # set of mixed data

data <- DataMix[,2:ncol(DataMix)]

rownames(data) <- DataMix[1:nrow(DataMix),1]

group.names = c("Grade Cafes/Work", "Formation/Dedication", "Coffees")

mf <- MFA(data, c(2,2,2), typegroups = c("n","c","f"), group.names) # performs MFA

tit <- c("Scree-Plot","Observations","Observations/Variables",
        "Correlation Circle","Inertia of the Variable Groups")

Plot.MFA(MFA = mf, titles = tit, xlabel = NA, ylabel = NA,
        posleg = 2, boxleg = FALSE, color = TRUE,
        groupcolor = c("blue3","red","goldenrod3"),
        namarr = FALSE, linlab = NA, savptc = FALSE,
        width = 3236, height = 2000, res = 300,
        casc = TRUE) # plotting several graphs on the screen

Plot.MFA(MFA = mf, titles = tit, xlabel = NA, ylabel = NA,
        posleg = 2, boxleg = FALSE, color = TRUE,
        namarr = FALSE, linlab = rep("A?",10),
        savptc = FALSE, width = 3236, height = 2000,
        res = 300, casc = TRUE) # plotting several graphs on the screen
```

---

Plot.PCA

*Graphs of the Principal Components Analysis (PCA).*

---

**Description**

Graphs of the Principal Components Analysis (PCA).

**Usage**

```
Plot.PCA(PC, titles = NA, xlabel = NA, ylabel = NA, size = 1.1,
         grid = TRUE, color = TRUE, linlab = NA, axes = TRUE, class = NA,
         classcolor = NA, posleg = 2, boxleg = TRUE, savptc = FALSE,
         width = 3236, height = 2000, res = 300, casc = TRUE)
```

**Arguments**

PC	Data of the PCA function.
titles	Titles of the graphics, if not set, assumes the default text.
xlabel	Names the X axis, if not set, assumes the default text.
ylabel	Names the Y axis, if not set, assumes the default text.
size	Size of the points in the graphs.
grid	Put grid on graphs (default = TRUE).
color	Colored graphics (default = TRUE).
linlab	Vector with the labels for the observations.
axes	Plots the X and Y axes (default = TRUE).
class	Vector with names of data classes.
classcolor	Vector with the colors of the classes.
posleg	0 with no caption, 1 for caption in the left upper corner, 2 for caption in the right upper corner (default), 3 for caption in the right lower corner, 4 for caption in the left lower corner.
boxleg	Puts the frame in the caption (default = TRUE).
savptc	Saves graphics images to files (default = FALSE).
width	Graphics images width when savptc = TRUE (default = 3236).
height	Graphics images height when savptc = TRUE (default = 2000).
res	Nominal resolution in ppi of the graphics images when savptc = TRUE (default = 300).
casc	Cascade effect in the presentation of the graphics (default = TRUE).

**Value**

Returns several graphs.

**Author(s)**

Paulo Cesar Ossani  
Marcelo Angelo Cirillo

**See Also**

[PCA](#)

**Examples**

```

data(iris) # data set

data <- iris[,1:4]

cls <- iris[,5] # data class

pc <- PCA(data, 2)

tit <- c("Scree-plot", "Observations", "Correlations")

cls <- as.character(iris[,5])

Plot.PCA(PC = pc, titles = tit, xlabel = NA, ylabel = NA,
         color = TRUE, linlab = NA, savptc = FALSE, size = 1.1,
         posleg = 2, boxleg = FALSE, class = cls, axes = TRUE,
         classcolor = c("blue3", "red", "goldenrod3"),
         width = 3236, height = 2000, res = 300, casc = FALSE)

```

---

Plot.PP

*Graphics of the Projection Pursuit (PP).*


---

**Description**

Graphics of the Projection Pursuit (PP).

**Usage**

```

Plot.PP(PP, titles = NA, xlabel = NA, ylabel = NA, posleg = 2, boxleg = TRUE,
        size = 1.1, grid = TRUE, color = TRUE, classcolor = NA, linlab = NA,
        axesvar = TRUE, axes = TRUE, savptc = FALSE, width = 3236, height = 2000,
        res = 300, casc = TRUE)

```

**Arguments**

PP	Data of the PP_Optimizer function.
titles	Titles of the graphics, if not set, assumes the default text.
xlabel	Names the X axis, if not set, assumes the default text.
ylabel	Names the Y axis, if not set, assumes the default text.
posleg	0 with no caption, 1 for caption in the left upper corner, 2 for caption in the right upper corner (default), 3 for caption in the right lower corner, 4 for caption in the left lower corner.
boxleg	Puts the frame in the caption (default = TRUE).

size	Size of the points in the graphs.
grid	Put grid on graphs (default = TRUE).
color	Colored graphics (default = TRUE).
classcolor	Vector with the colors of the classes.
linlab	Vector with the labels for the observations.
axesvar	Puts axes of rotation of the variables, only when dimproj > 1 (default = TRUE).
axes	Plots the X and Y axes (default = TRUE).
savptc	Saves graphics images to files (default = FALSE).
width	Graphics images width when savptc = TRUE (default = 3236).
height	Graphics images height when savptc = TRUE (default = 2000).
res	Nominal resolution in ppi of the graphics images when savptc = TRUE (default = 300).
casc	Cascade effect in the presentation of the graphics (default = TRUE).

**Value**

Graph of the evolution of the indices, and graphs whose data were reduced in two dimensions.

**Author(s)**

Paulo Cesar Ossani  
Marcelo Angelo Cirillo

**See Also**

[PP\\_Optimizer](#) and [PP\\_Index](#)

**Examples**

```
data(iris) # dataset

# Example 1 - Without the classes in the data
data <- iris[,1:4]

findex <- "kurtosismax" # index function

dim <- 1 # dimension of data projection

sphere <- TRUE # spherical data

res <- PP_Optimizer(data = data, class = NA, findex = findex,
                    optmethod = "GTSA", dimproj = dim, sphere = sphere,
                    weight = TRUE, lambda = 0.1, r = 1, cooling = 0.9,
                    eps = 1e-3, maxiter = 500, half = 30)

Plot.PP(res, titles = NA, posleg = 1, boxleg = FALSE, color = TRUE,
         linlab = NA, axesvar = TRUE, axes = TRUE, savptc = FALSE,
```

```

width = 3236, height = 2000, res = 300, casc = FALSE)

# Example 2 - With the classes in the data
class <- iris[,5] # data class

res <- PP_Optimizer(data = data, class = class, findex = findex,
  optmethod = "GTSA", dimproj = dim, sphere = sphere,
  weight = TRUE, lambda = 0.1, r = 1, cooling = 0.9,
  eps = 1e-3, maxiter = 500, half = 30)

tit <- c(NA,"Graph example") # titles for the graphics

Plot.PP(res, titles = tit, posleg = 1, boxleg = FALSE, color = TRUE,
  classcolor = c("blue3","red","goldenrod3"), linlab = NA,
  axesvar = TRUE, axes = TRUE, savptc = FALSE, width = 3236,
  height = 2000, res = 300, casc = FALSE)

# Example 3 - Without the classes in the data, but informing
#           the classes in the plot function
res <- PP_Optimizer(data = data, class = NA, findex = "Moment",
  optmethod = "GTSA", dimproj = 2, sphere = sphere,
  weight = TRUE, lambda = 0.1, r = 1, cooling = 0.9,
  eps = 1e-3, maxiter = 500, half = 30)

lin <- c(rep("a",50),rep("b",50),rep("c",50)) # data class

Plot.PP(res, titles = NA, posleg = 1, boxleg = FALSE, color = TRUE,
  linlab = lin, axesvar = TRUE, axes = TRUE, savptc = FALSE,
  width = 3236, height = 2000, res = 300, casc = FALSE)

# Example 4 - With the classes in the data, but not informed in plot function
class <- iris[,5] # data class

dim <- 2 # dimension of data projection

findex <- "lda" # index function

res <- PP_Optimizer(data = data, class = class, findex = findex,
  optmethod = "GTSA", dimproj = dim, sphere = sphere,
  weight = TRUE, lambda = 0.1, r = 1, cooling = 0.9,
  eps = 1e-3, maxiter = 500, half = 30)

tit <- c("",NA) # titles for the graphics

Plot.PP(res, titles = tit, posleg = 1, boxleg = FALSE, color = TRUE,
  linlab = NA, axesvar = TRUE, axes = TRUE, savptc = FALSE,
  width = 3236, height = 2000, res = 300, casc = FALSE)

```

---

Plot.Regr                      *Graphs of the linear regression results.*

---

### Description

Graphs of the linear regression results.

### Usage

```
Plot.Regr(Reg, typegraf = "Scatterplot", title = NA, xlabel = NA,
          ylabel = NA, namevary = NA, namevarx = NA, size = 1.1,
          grid = TRUE, color = TRUE, intconf = TRUE, intprev = TRUE,
          savptc = FALSE, width = 3236, height = 2000, res = 300,
          casc = TRUE)
```

### Arguments

Reg	Regression function data.
typegraf	Type of graphic: "Scatterplot" - Scatterplot 2 to 2, "Regression" - Graph of the linear regression, "QQPlot" - Graph of the normal probability of the residues, "Histogram" - Histogram of the residues, "Fits" - Graph of the adjusted values versus residuals, "Order" - Graph of the order of the observations versus the residuals.
title	Titles of the graphics, if not set, assumes the default text.
xlabel	Names the X axis, if not set, assumes the default text.
ylabel	Names the Y axis, if not set, assumes the default text.
namevary	Variable name Y, if not set, assumes the default text.
namevarx	Name of the variable X, or variables X, if not set, assumes the default text.
size	Size of the points in the graphs.
grid	Put grid on graphs (default = TRUE).
color	Colored graphics (default = TRUE).
intconf	Case typegraf = "Regression". Graphics with confidence interval (default = TRUE).
intprev	Case typegraf = "Regression". Graphics with predictive interval (default = TRUE).
savptc	Saves graphics images to files (default = FALSE).
width	Graphics images width when savptc = TRUE (default = 3236).
height	Graphics images height when savptc = TRUE (default = 2000).
res	Nominal resolution in ppi of the graphics images when savptc = TRUE (default = 300).
casc	Cascade effect in the presentation of the graphics (default = TRUE).

**Value**

Returns several graphs.

**Author(s)**

Paulo Cesar Ossani

**See Also**

[Regr](#)

**Examples**

```
data(DataMix)

Y <- DataMix[,2]

X <- DataMix[,7]

name.y <- "Medium grade"

name.x <- "Commercial coffees"

res <- Regr(Y, X, namevarx = name.x , intercept = TRUE, sigf = 0.05)

tit <- c("Scatterplot")
Plot.Regr(res, typegraf = "Scatterplot", title = tit,
          namevary = name.y, namevarx = name.x, color = TRUE,
          savptc = FALSE, width = 3236, height = 2000, res = 300)

tit <- c("Scatterplot with the adjusted line")
Plot.Regr(res, typegraf = "Regression", title = tit,
          xlabel = name.x, ylabel = name.y, color = TRUE,
          intconf = TRUE, intprev = TRUE, savptc = FALSE,
          width = 3236, height = 2000, res = 300)

dev.new() # necessary to not overlap the following graphs to the previous graph

par(mfrow = c(2,2))

Plot.Regr(res, typegraf = "QQPlot", casc = FALSE)
Plot.Regr(res, typegraf = "Histogram", casc = FALSE)
Plot.Regr(res, typegraf = "Fits", casc = FALSE)
Plot.Regr(res, typegraf = "Order", casc = FALSE)
```

**Description**

Function used to find Projection Pursuit indexes (PP).

**Usage**

```
PP_Index(data, class = NA, vector.proj = NA,
         findindex = "HOLES", dimproj = 2, weight = TRUE,
         lambda = 0.1, r = 1, ck = NA)
```

**Arguments**

<code>data</code>	Numeric dataset without class information.
<code>class</code>	Vector with names of data classes.
<code>vector.proj</code>	Vector projection.
<code>findindex</code>	Projection index function to be used: "lda" - LDA index, "pda" - PDA index, "lr" - Lr index, "holes" - Holes index (default), "cm" - Central Mass index, "pca" - PCA index, "friedmantukey" - Friedman Tukey index, "entropy" - Entropy index, "legendre" - Legendre index, "laguerrefourier" - Laguerre Fourier index, "hermite" - Hermite index, "naturalhermite" - Natural Hermite index, "kurtosismax" - Maximum kurtosis index, "kurtosismin" - Minimum kurtosis index, "moment" - Moment index, "mf" - MF index, "chi" - Chi-square index.
<code>dimproj</code>	Dimension of data projection (default = 2).
<code>weight</code>	Used in index LDA, PDA and Lr to weight the calculations for the number of elements in each class (default = TRUE).
<code>lambda</code>	Used in the PDA index (default = 0.1).
<code>r</code>	Used in the Lr index (default = 1).
<code>ck</code>	Internal use of the CHI index function.

**Value**

<code>num.class</code>	Number of classes.
<code>class.names</code>	Class names.
<code>findindex</code>	Projection index function used.
<code>vector.proj</code>	Projection vectors found.
<code>index</code>	Projection index found in the process.

**Author(s)**

Paulo Cesar Ossani  
Marcelo Angelo Cirillo

**References**

- Ossani, P. C.; Figueira, M. R.; Cirillo, M. A. Proposition of a new index for projection pursuit in the multiple factor analysis. *Computational and Mathematical Methods*, v. 1, p. 1-18, 2020.
- Cook, D.; Buja, A.; Cabrera, J. Projection pursuit indexes based on orthonormal function expansions. *Journal of Computational and Graphical Statistics*, 2(3):225-250, 1993.
- Cook, D.; Buja, A.; Cabrera, J.; Hurley, C. Grand tour and projection pursuit, *Journal of Computational and Graphical Statistics*, 4(3), 155-172, 1995.
- Cook, D.; Swayne, D. F. Interactive and Dynamic Graphics for data Analysis: With R and GGobi. Springer. 2007.
- Espezua, S.; Villanueva, E.; Maciel, C. D.; Carvalho, A. A projection pursuit framework for supervised dimension reduction of high dimensional small sample datasets. *Neurocomputing*, 149, 767-776, 2015.
- Friedman, J. H., Tukey, J. W. A projection pursuit algorithm for exploratory data analysis. *IEEE Transaction on Computers*, 23(9):881-890, 1974.
- Hastie, T., Buja, A., Tibshirani, R. Penalized discriminant analysis. *The Annals of Statistics*. 23(1), 73-102 . 1995.
- Huber, P. J. Projection pursuit. *Annals of Statistics*, 13(2):435-475, 1985.
- Jones, M. C.; Sibson, R. What is projection pursuit, (with discussion), *Journal of the Royal Statistical Society, Series A* 150, 1-36, 1987.
- Lee, E. K.; Cook, D. A projection pursuit index for large p small n data. *Statistics and Computing*, 20(3):381-392, 2010.
- Lee, E.; Cook, D.; Klinke, S.; Lumley, T. Projection pursuit for exploratory supervised classification. *Journal of Computational and Graphical Statistics*, 14(4):831-846, 2005.
- Martinez, W. L., Martinez, A. R.; *Computational Statistics Handbook with MATLAB*, 2th. ed. New York: Chapman & Hall/CRC, 2007. 794 p.
- Martinez, W. L.; Martinez, A. R.; Solka, J. *Exploratory data Analysis with MATLAB*, 2th. ed. New York: Chapman & Hall/CRC, 2010. 499 p.
- Pena, D.; Prieto, F. Cluster identification using projections. *Journal of the American Statistical Association*, 96(456):1433-1445, 2001.
- Posse, C. Projection pursuit exploratory data analysis, *Computational Statistics and data Analysis*, 29:669-687, 1995a.
- Posse, C. Tools for two-dimensional exploratory projection pursuit, *Journal of Computational and Graphical Statistics*, 4:83-100, 1995b.

**See Also**

[PP\\_Optimizer](#) and [Plot.PP](#)

**Examples**

```

data(iris) # data set

data <- iris[,1:4]

# Example 1 - Without the classes in the data
ind <- PP_Index(data = data, class = NA, vector.proj = NA,
               findex = "moment", dimproj = 2, weight = TRUE,
               lambda = 0.1, r = 1)

print("Number of classes:"); ind$num.class
print("class Names:"); ind$class.names
print("Projection index function:"); ind$findex
print("Projection vectors:"); ind$vector.proj
print("Projection index:"); ind$index

# Example 2 - With the classes in the data
class <- iris[,5] # data class

findex <- "pda" # index function

sphere <- TRUE # spherical data

res <- PP_Optimizer(data = data, class = class, findex = findex,
                   optmethod = "SA", dimproj = 2, sphere = sphere,
                   weight = TRUE, lambda = 0.1, r = 1, cooling = 0.9,
                   eps = 1e-3, maxiter = 1000, half = 30)

# Comparing the result obtained
if (match(toupper(findex),c("LDA", "PDA", "LR"), nomatch = 0) > 0) {
  if (sphere) {
    data <- apply(predict(prcomp(data)), 2, scale) # spherical data
  }
} else data <- as.matrix(res$proj.data[,1:Dim])

ind <- PP_Index(data = data, class = class, vector.proj = res$vector.opt,
               findex = findex, dimproj = 2, weight = TRUE, lambda = 0.1,
               r = 1)

print("Number of classes:"); ind$num.class
print("class Names:"); ind$class.names
print("Projection index function:"); ind$findex
print("Projection vectors:"); ind$vector.proj
print("Projection index:"); ind$index
print("Optimized Projection index:"); res$index[length(res$index)]

```

**Description**

Optimization function of the Projection Pursuit index (PP).

**Usage**

```
PP_Optimizer(data, class = NA, findex = "HOLES",
             dimproj = 2, sphere = TRUE, optmethod = "GTSA",
             weight = TRUE, lambda = 0.1, r = 1, cooling = 0.9,
             eps = 1e-3, maxiter = 3000, half = 30)
```

**Arguments**

data	Numeric dataset without class information.
class	Vector with names of data classes.
findex	Projection index function to be used: "lda" - LDA index, "pda" - PDA index, "lr" - Lr index, "holes" - Holes index (default), "cm" - Central Mass index, "pca" - PCA index, "friedmantukey" - Friedman Tukey index, "entropy" - Entropy index, "legendre" - Legendre index, "laguerrefourier" - Laguerre Fourier index, "hermite" - Hermite index, "naturalhermite" - Natural Hermite index, "kurtosismax" - Maximum kurtosis index, "kurtosismin" - Minimum kurtosis index, "moment" - Moment index, "mf" - MF index, "chi" - Chi-square index.
dimproj	Dimension of the data projection (default = 2).
sphere	Spherical data (default = TRUE).
optmethod	Optimization method GTSA - Grand Tour Simulated Annealing or SA - Simulated Annealing (default = "GTSA").
weight	Used in index LDA, PDA and Lr to weight the calculations for the number of elements in each class (default = TRUE).
lambda	Used in the PDA index (default = 0.1).
r	Used in the Lr index (default = 1).
cooling	Cooling rate (default = 0.9).
eps	Approximation accuracy for cooling (default = 1e-3).
maxiter	Maximum number of iterations of the algorithm (default = 3000).
half	Number of steps without incrementing the index, then decreasing the cooling value (default = 30).

**Value**

num.class	Number of classes.
class.names	Class names.
proj.data	Projected data.
vector.opt	Projection vectors found.
index	Vector with the projection indices found in the process, converging to the maximum, or the minimum.
findex	Projection index function used.

**Author(s)**

Paulo Cesar Ossani  
 Marcelo Angelo Cirillo

**References**

Cook, D.; Lee, E. K.; Buja, A.; Wickham, H. Grand tours, projection pursuit guided tours and manual controls. In Chen, Chunhouh, Hardle, Wolfgang, Unwin, e Antony (Eds.), *Handbook of data Visualization*, Springer Handbooks of Computational Statistics, chapter III.2, p. 295-314. Springer, 2008.

Lee, E.; Cook, D.; Klinke, S.; Lumley, T. Projection pursuit for exploratory supervised classification. *Journal of Computational and Graphical Statistics*, 14(4):831-846, 2005.

**See Also**

[Plot.PP](#) and [PP\\_Index](#)

**Examples**

```
data(iris) # data set

# Example 1 - Without the classes in the data
data <- iris[,1:4]

class <- NA # data class

findex <- "kurtosismax" # index function

dim <- 1 # dimension of data projection

sphere <- TRUE # spherical data

res <- PP_Optimizer(data = data, class = class, findex = findex,
                    optmethod = "GTSA", dimproj = dim, sphere = sphere,
                    weight = TRUE, lambda = 0.1, r = 1, cooling = 0.9,
                    eps = 1e-3, maxiter = 1000, half = 30)

print("Number of classes:"); res$num.class
```

```

print("class Names:"); res$class.names
print("Projection index function:"); res$findex
print("Projected data:"); res$proj.data
print("Projection vectors:"); res$vector.opt
print("Projection index:"); res$index

# Example 2 - With the classes in the data
class <- iris[,5] # classe dos dados

res <- PP_Optimizer(data = data, class = class, findex = findex,
                    optmethod = "GTSA", dimproj = dim, sphere = sphere,
                    weight = TRUE, lambda = 0.1, r = 1, cooling = 0.9,
                    eps = 1e-3, maxiter = 1000, half = 30)

print("Number of classes:"); res$num.class
print("class Names:"); res$class.names
print("Projection index function:"); res$findex
print("Projected data:"); res$proj.data
print("Projection vectors:"); res$vector.opt
print("Projection index:"); res$index

```

---

Regr

*Linear regression.*


---

### Description

Performs linear regression on a data set.

### Usage

```
Regr(Y, X, namevarx = NA, intercept = TRUE, sigf = 0.05)
```

### Arguments

Y	Variable response.
X	Regression variables.
namevarx	Name of the variable, or variables X, if not set, assumes the default text.
intercept	Consider the intercept in the regression (default = TRUE).
sigf	Level of significance of residue tests(default = 5%).

### Value

Betas	Regression coefficients.
CovBetas	Covariance matrix of the regression coefficients.
ICc	Confidence interval of the regression coefficients.
hip.test	Hypothesis test of the regression coefficients.

ANOVA	Regression analysis of the variance.
R	Determination coefficient.
Rc	Corrected coefficient of determination.
Ra	Adjusted coefficient of determination.
QME	Variance of the residues.
ICQME	Confidence interval of the residue variance.
prev	Prediction of the regression fit.
IPp	Predictions interval
ICp	Interval of prediction confidence
error	Residuals of the regression fit.
error.test	It returns to 5% of significance the test of independence, normality and homogeneity of the variance of the residues.

**Author(s)**

Paulo Cesar Ossani

**References**

- Charnet, R.; at al.. *Analise de modelos de regressao lienar*, 2a ed. Campinas: Editora da Unicamp, 2008. 357 p.
- Rencher, A. C.; Schaalje, G. B. *Linear models in statistcic*. 2th. ed. New Jersey: John & Sons, 2008. 672 p.
- Rencher, A. C. *Methods of multivariate analysis*. 2th. ed. New York: J.Wiley, 2002. 708 p.

**See Also**

[Plot.Regr](#)

**Examples**

```
data(DataMix)

Y <- DataMix[,2]

X <- DataMix[,6:7]

name.x <- c("Special Coffees", "Commercial Coffees")

res <- Regr(Y, X, namevarx = name.x , intercept = TRUE, sigf = 0.05)

print("Regression Coefficients:"); round(res$Betas,4)
print("Analysis of Variance:"); res$ANOVA
print("Hypothesis test of regression coefficients:"); round(res$hip.test,4)
print("Determination coefficient:"); round(res$R,4)
print("Corrected coefficient of determination:"); round(res$Rc,4)
print("Adjusted coefficient of determination:"); round(res$Ra,4)
print("Tests of the residues"); res$error.test
```

---

 Scatter

*Scatter plot.*


---

**Description**

Performs the scatter plot.

**Usage**

```
Scatter(data, ellipse = TRUE, ellipse.level = 0.95, rectangle = FALSE,
        title = NA, xlabel = NA, ylabel = NA, posleg = 2, boxleg = TRUE,
        axes = TRUE, size = 1.1, grid = TRUE, color = TRUE, linlab = NA,
        class = NA, classcolor = NA, savptc = FALSE, width = 3236,
        height = 2000, res = 300)
```

**Arguments**

<code>data</code>	Data with x and y coordinates.
<code>ellipse</code>	Place an ellipse around the classes (default = TRUE).
<code>ellipse.level</code>	Significance level of the ellipse (default = 0.95).
<code>rectangle</code>	Place rectangle to differentiate classes (default = FALSE).
<code>title</code>	Titles of the graphics, if not set, assumes the default text.
<code>xlabel</code>	Names the X axis, if not set, assumes the default text.
<code>ylabel</code>	Names the Y axis, if not set, assumes the default text.
<code>posleg</code>	0 with no caption, 1 for caption in the left upper corner, 2 for caption in the right upper corner (default), 3 for caption in the right lower corner, 4 for caption in the left lower corner.
<code>boxleg</code>	Puts the frame in the caption (default = TRUE).
<code>axes</code>	Plots the X and Y axes (default = TRUE).
<code>size</code>	Size of the points in the graphs.
<code>grid</code>	Put grid on graphs (default = TRUE).
<code>color</code>	Colored graphics (default = TRUE).
<code>linlab</code>	Vector with the labels for the observations.
<code>class</code>	Vector with names of data classes.
<code>classcolor</code>	Vector with the colors of the classes.
<code>savptc</code>	Saves graphics images to files (default = FALSE).
<code>width</code>	Graphics images width when savptc = TRUE (default = 3236).
<code>height</code>	Graphics images height when savptc = TRUE (default = 2000).
<code>res</code>	Nominal resolution in ppi of the graphics images when savptc = TRUE (default = 300).

**Value**

Scatter plot.

**Author(s)**

Paulo Cesar Ossani

**References**

Rencher, A. C. *Methods of multivariate analysis*. 2th. ed. New York: J.Wiley, 2002. 708 p.  
Anton, H.; Rorres, C. *Elementary linear algebra: applications version*. 10th ed. New Jersey: John Wiley & Sons, 2010. 768 p.

**Examples**

```
data(iris) # data set
```

```
data <- iris[,3:4]
```

```
cls <- iris[,5] # data class
```

```
Scatter(data, ellipse = TRUE, ellipse.level = 0.95, rectangle = FALSE,  
        title = NA, xlabel = NA, ylabel = NA, posleg = 1, boxleg = FALSE,  
        axes = FALSE, size = 1.1, grid = TRUE, color = TRUE, linlab = NA,  
        class = cls, classcolor = c("goldenrod3", "blue", "red"),  
        savptc = FALSE, width = 3236, height = 2000, res = 300)
```

```
Scatter(data, ellipse = FALSE, ellipse.level = 0.95, rectangle = TRUE,  
        title = NA, xlabel = NA, ylabel = NA, posleg = 1, boxleg = TRUE,  
        axes = FALSE, size = 1.1, grid = TRUE, color = TRUE, linlab = NA,  
        class = cls, classcolor = c("goldenrod3", "blue", "red"),  
        savptc = FALSE, width = 3236, height = 2000, res = 300)
```

# Index

- \* **Analysis of canonical correlation**
  - CCA, 9
  - Plot.CCA, 39
- \* **Biplot**
  - Biplot, 6
- \* **CA**
  - CA, 8
  - Plot.CA, 37
- \* **CCA**
  - CCA, 9
  - Plot.CCA, 39
- \* **CI**
  - CI, 11
  - Plot.CI, 41
- \* **Cluster Analysis**
  - Cluster, 13
- \* **Cluster**
  - Cluster, 13
- \* **CoefVar**
  - CoefVar, 15
- \* **Coefficient of variation**
  - CoefVar, 15
- \* **Confidence Intervals**
  - CI, 11
  - Plot.CI, 41
- \* **Correspondence Analysis**
  - Plot.CA, 37
- \* **Data set**
  - DataCoffee, 18
  - DataFreq, 19
  - DataInd, 20
  - DataMix, 21
  - DataQuali, 21
  - DataQuan, 22
- \* **Dummy variables**
  - IM, 28
- \* **FA**
  - FA, 23
  - Plot.FA, 43
- \* **Factor Analysis**
  - FA, 23
  - Plot.FA, 43
- \* **GSVD**
  - GSVD, 27
- \* **Generalized Singular Value Decomposition**
  - GSVD, 27
- \* **Grand Tour**
  - GrandTour, 25
- \* **Indicator matrix**
  - IM, 28
- \* **LDA**
  - DA, 16
- \* **Linear and quadratic discriminant analysis**
  - DA, 16
- \* **MCA**
  - CA, 8
- \* **MDS**
  - MDS, 30
- \* **MFACT**
  - MFA, 31
  - Plot.MFA, 45
- \* **MFA**
  - MFA, 31
  - Plot.MFA, 45
- \* **Multidimensional Scaling**
  - MDS, 30
- \* **Multiple Correspondence Analysis**
  - CA, 8
- \* **Multiple Factor Analysis**
  - MFA, 31
  - Plot.MFA, 45
- \* **Multivariate Analysis**
  - MVar-package, 2
- \* **NormTest**
  - NormTest, 35
- \* **Normalizes the data.**

- NormData, 34
  - \* **PCA**
    - PCA, 36
    - Plot.PCA, 46
  - \* **PP**
    - Plot.PP, 48
    - PP\_Index, 52
    - PP\_Optimizer, 55
  - \* **Plot.Cor**
    - Plot.Cor, 42
  - \* **Principal Components Analysis**
    - PCA, 36
    - Plot.PCA, 46
  - \* **Projection pursuit**
    - Plot.PP, 48
    - PP\_Index, 52
    - PP\_Optimizer, 55
  - \* **QDA**
    - DA, 16
  - \* **Regression**
    - Plot.Regr, 51
    - Regr, 58
  - \* **Scatter Plot**
    - Scatter, 60
  - \* **Simple Correspondence Analysis**
    - CA, 8
  - \* **Test of normality of the data.**
    - NormTest, 35
- Biplot, 6
- CA, 8, 38
- CCA, 9, 40
- CI, 11, 41
- Cluster, 13
- CoefVar, 15
- DA, 16
- DataCoffee, 18
- DataFreq, 19
- DataInd, 20
- DataMix, 21
- DataQuali, 21
- DataQuan, 22
- FA, 23, 44
- GrandTour, 25
- GSVD, 27
- IM, 28
- LocLab, 29
- MDS, 30
- MFA, 31, 46
- MVar-package, 2
- NormData, 34
- NormTest, 35
- PCA, 36, 47
- Plot.CA, 9, 37
- Plot.CCA, 11, 39
- Plot.CI, 12, 41
- Plot.Cor, 42
- Plot.FA, 24, 43
- Plot.MFA, 33, 45
- Plot.PCA, 37, 46
- Plot.PP, 48, 54, 57
- Plot.Regr, 51, 59
- PP\_Index, 49, 52, 57
- PP\_Optimizer, 49, 54, 55
- Regr, 52, 58
- Scatter, 60